



# Key Switches



Panel hole 19mm. 33.6mm overall depth. 61mm depth with key inserted, including terminals. Two keys supplied. Rated 2A @ 250V AC, 4A @ 125V AC, 4A @ 28V DC. 003 key models can only be ordered by OEM customers. MOQ applies.

Part No. / Key	Configuration	Poles	Pos 1	Pos 2	Pos 3	Pos 4	Key Removeable
S 2600 Random S 2604 606 Key S 2605 003 Key		DP	8-1, 4-5	1-3, 5-7	-	-	Pos. 1
S 2601 Random S 2603 606 Key		DP	8-1, 4-5	1-2, 5-6	-	-	Pos. 1
S 2612 003 S 2614 606		DP	8-1, 4-5	1-3, 5-7	-	-	Pos. 1 & 2
S 2620 Random S 2622 003 S 2624 606		DP	8-1, 4-5	1-2, 5-6	7-8, 3-4	-	Pos. 1
S 2625 003		DP	8-1, 4-5	1-2, 5-6	2-3, 6-7	-	Pos. 1
S 2632 606		DP	8-1, 4-5	1-2, 5-6	7-8, 3-4	-	Pos. 1, 2 & 3
S 2623 003		DP	8-1, 4-5	1-2, 5-6	2-3, 6-7	-	Pos. 3
S 2654 606		DP	8-1	1-2	2-3	3-4	Pos. 1, 2, 3 & 4.

▲ Momentary   ● Removeable   ● Trapped