

CS-64BS

WIDE RANGE SPEAKER

The CS-64BS is the voice alarm certification product. The CS-64BS Wide range speaker features an ABS resin enclosure and stainless steel bracket for all weather durability. It is comprised of a high-efficiency weather-resistant horn and a high quality sound cone speaker, providing clear and highly directional sound reproduction.



Article number:CS-64BS
Alternative products: CS-154BS

Specifications

Sensitivity (1#W, 1#m)	96 dB 1 W, 1 m at 330 Hz to 3.3 kHz pink noise 93 dB (1 W, 1 m at 100 Hz to 10 kHz pink noise) 81 dB (1 W, 4 m at 100 Hz to 10 kHz pink noise)
Frequency response.	130 Hz - 13 kHz
Max. SPL (1 m)	100 dB 6 W, 1 m at 100 Hz to 10 kHz pink noise 88 dB (6 W, 4 m at 100 Hz to 10 kHz pink noise)
Tappings	100 V : 1.7 kΩ (6 W) / 3.3 kΩ (3 W) / 10 kΩ (1 W) 70 V : 830 Ω (6 W) / 1.7 kΩ (3 W) / 3.3 kΩ (1.5 W) / 10 kΩ (0.5 W)
Speaker component	12 cm cone-type (treated for splash proof)
Finish.	ABS resin, paint, papyrus white (RAL 9018 or equivalent), Bracket: Stainless steel
Operating temperature.	-20 °C to +55 °C (-4 °F to 131 °F)

CS-64BS

WIDE RANGE SPEAKER

Appearance

