



- 170° angle wide view camera
 - Audio & visual guidance to provide visitors status and operation assistance
 - Search names and numbers using the keypad
 - Customer programmable welcome messages can be displayed
 - 9 languages (English, French, German, Spanish, Dutch, Italian, Norwegian*¹, Turkish*¹ and Finnish*¹) are available for messages on Guidance display
 - 6 languages (English, French, German, Spanish, Dutch and Norwegian*²) are available for audio guidance
 - White light LED illuminates automatically in low-light conditions
- *1: GT-DMA, GT-NS not available
*2: GT-DMA, GT-DA, GT-DA-L not available



GT-4F
4-module front frame
GF-3F
3-module front frame
GF-2F
2-module front frame



GT-4B
4-module back box
GF-3B
3-module back box
GF-2B
2-module back box



GT-nH
Rain hood



GT-nHB
Hooded surface-mount box



SBX-GTDM
Surface Mount Box for GT-DM

Call switch Module



GF-1P
1-call panel



GF-2P
2-call panel



GF-3P
3-call panel



GF-4P
4-call panel



GT-SW
Call switch module

Digital name scrolling module



GT-NSP-L
Display module panel



GT-NSB
Digital name scroll display module for GT-DB(-VN)
Available 3rd Quarter 2017



GT-NS
Digital name scroll display module for GT-DA(-L)

Front frame & back box



GF-10KP
10-key module panel



GT-10K
10-key module

Access control keypad module



GT-AC
Access control keypad module



GT-HID
Card reader panel

Option



GF-AP
Address panel



GT-AD
Address module



GF-BP
Blank panel

Specifications (GT-SW,GT-10K,GT-AD)

Lighting	Yellow LED
Material	Fire-retardant ABS plastic

Specifications (GT-NSB,GT-NS)

Power source	24V DC, supplied by PS-2420
Material	GT-NSB: Self-extinguishing ABS resin GT-NS: Fire-retardant ABS plastic

* GT-NS cannot be used in the tenant sections and common sections of a multi building systems.