

# Video Multi-Tenant System

## Entrance station

### All-in-one type



#### GT-DMB-N

Entrance station  
W/NFC reader  
(Back box not included.)  
Use GF-3B.

### Module type



#### Camera Module



**GT-VP**  
Camera panel



**GT-VB**  
Camera module  
for GT-DB(-VN)

#### Audio Module



**GT-DBP**  
Audio panel  
for GT-DB(-VN)



**GT-DB**  
Audio module  
W/O NFC reader



**GT-DB-VN**  
Audio module  
W/NFC reader

#### Digital name scrolling module



**GT-NSP-L**  
Display module panel



**GT-NSB**  
Digital name scroll  
display module for GT-DB(-VN)

### Specifications (GT-DMB-N)

Power source	24V DC, supplied from PS-2420S, PS-2420UL, PS-2420BF, PS-2420DM, PS-2420
Video monitor	3.5 inch TFT color LCD
Camera	1/4 inch color CMOS
Communication	Open voice hands-free communication
Mounting	Flush wall-mount
Material	Panel: Stainless steel Case: Self-extinguishing ABS resin
IP rating	IP54
IK rating	IK07

### Specifications (GT-VB,GT-DB,GT-DB-VN)

Camera	GT-VB: 1/4 inch color CMOS
Communication	GT-DB, GT-DB-VN: Open voice hands-free communication
Wiring	Two single-pair cable common
Type of cable	2-conductor cable solid copper & non-braided, polyethylene insulation, 0.65mm dia.~1.0mm dia.
Mounting	Box and front frame GF-2B, 3B and GT-4B, and GF-2F, 3F and GT-4F
Material	GT-VB: Self-extinguishing PC + ABS resin GT-DB-VN: Self-extinguishing ABS resin

\* GT-DB and GT-DB-VN cannot be used in the main sections of a multi building systems.

### Specifications (GT-NSB)

Power source	24V DC, supplied from PS-2420S, PS-2420UL, PS-2420BF, PS-2420DM, PS-2420
Material	Self-extinguishing ABS resin