

Hands-Free Color Video Multi-tenant Building System with Zoom & PanTilt

Entrance station


All-in-one type



GT-DMB-N
Available 3rd Quarter 2017
W/NFC reader
(Back box not included.)
Use GF-3B.

GT-DMA
Available 1st Quarter 2017
W/O NFC reader

Module type



Camera Module



GT-VP
Camera panel



GT-VB
Camera module
for GT-DB(-VN)
Available 3rd Quarter 2017



GT-VAA
Camera module
for GT-DA(-L)
Available 1st Quarter 2017

Audio Module



GT-DBP
Audio panel
for GT-DB(-VN)
Available 3rd Quarter 2017



GT-DB
Audio module
W/O NFC reader
Available 3rd Quarter 2017



GT-DB-VN
Audio module
W/NFC reader
Available 3rd Quarter 2017



GT-DP
Audio panel
for GT-DA



GT-DA
Audio module



GT-DP-L
Audio panel
for GT-DA-L



GT-DA-L
Audio module
W/guide display

Specifications (GT-DMB-N,GT-DMA)

Power source	24V DC, supplied by PS-2420
Video monitor	3.5-inch TFT color LCD
Camera	1/4-inch color CMOS
Communication	Open voice hands-free communication
Mounting	Flush wall-mount
Material	Stainless steel
IP rating	IP54
IK rating	IK07

* GT-DMA cannot be used in the tenant sections and common sections of a multi building systems.

Specifications (GT-VB,GT-VAA,GT-DB,GT-DB-VN,GT-DA,GT-DA-L)

Camera	GT-VB, GT-VAA : 1/4-inch color CMOS
Communication	GT-DB, GT-DB-VN, GT-DA, GT-DA-L : Open voice hands-free communication
Wiring	Two single-pair cable common
Type of cable	2-conductor cable solid copper & non-braided, polyethylene insulation, 0.65mm dia.~1.0mm dia.
Mounting	Box and front frame GF-2B, 3B and GT-4B, and GF-2F, 3F and GT-4F
Material	GT-VB, GT-VAA: Self-extinguishing PC + ABS resin GT-DB, GT-DB-VN: Self-extinguishing ABS resin GT-DA, GT-DA-L: Fire-retardant plastic

* GT-DB and GT-DB-VN cannot be used in the common sections of a multi building systems.

* GT-DA and GT-DA-L cannot be used in the tenant sections and common sections of a multi building systems.