


■ SPECIFICATIONS


	1					
Power source	Supplied from Master monitor station or Expansion monitor station					
Type of communication	Open voice hands-free communication					
Camera	1/4 inch color CMOS					
Minimum illumination	5 lux (approx.)					
Ambient temperature	-20~+60°C					
Mounting	Flush mount					
Electrical box	Not used(Mounts on built-in back box)					
Material	Front panel: Stainless steel. Main unit: Self-extinguishing PC + ABS resin					
Weight	580g (approx.) (1.27 lbs)					
Unit color	Front panel: Silver (Stainless steel, vertical hair-line processed.)					
diffe color	Back box: Black					
IP rating	IP54					
IK rating	IK07					
DESCRIPTION (Color,		FIG. NAME		UNIT	DATE	
VIDEO DOOR STATION Vandal-resistant)		PRODUCT DRAWING/SPECIFICATIONS		mm	3 December, 2018	
MODEL NO.		FIG. NO.	PAGE	REVISION	AIRUANE	
JO-DVF		59295-1-2	1/2	2	AIPHONE	


■WIRING DIAGRAM



■ IMAGE VIEW AREA & MOUNTING HEIGHT









* The figures are approximate.

■RESTRICTIONS


- Do not have rain escape openings on bottom covered with caulking seals.
- JO-DVF door station is exclusively used for JO Series.
- Avoid installing JO-DVF door station in the following locations;



At the entrance where background is sky in upper floors of building, etc.



The background of the standing caller's is white wall.



Where the standing location is strongly sunlit.

■FUNCTIONS

- Initiating a call to and entering communication with Master monitor station or Expansion monitor station.
- Name plate is backlit constantly.
- White light LED turns on during low-light conditions when monitoring and talking status.

DESCRIPTION (Color, FIG. NAME		FIG. NAME		UNIT	DATE
VIDEO DOOR STATION	Vandal-resistant)	WIRING/IMAGE/RESTR./FCN.		mm	10 June, 2013
MODEL NO.		FIG. NO.	PAGE	REVISION	AIRIIANE
JO-DVF		59295-2-2	2/2	1	AIPHONE