
# **4G Video Intercom & PMS**



### **Features:**

- ◆ 4G IP videophone
- Instant videocall to mobile app
- 24/7 video recording
- ◆ Face detection alarm
- ◆ Max. 1000 room numbers.
- Max. 1000 Mifare cards (optional)

- ◆ Max. 2000 PIN codes
- ◆ 4G LTE/3G/GSM network
- ◆ 1080P H.265 video
- ◆ 2-way audio
- ◆ SD card storage up to 128GB
- ◆ Power: DC 12V-18V 1A

# **APP (Door intercom):**

- Add/delete/modify user's room number/phone number/password/ Mifare card.
- Unlock door remotely via APP
- Manage multiple devices
- Play video record
- Check log of unlocking
- Door unlock/lock notifications and offline alert to APP





# **Specifications**

	Andri	ANI4042	
Model		AN1912	
Video	Image Sensor	1/2.7" 2MP CMOS	
	Image Compression	H.265	
	Image Frame Rate	25fps maximum	
	Resolution	1080P(1920 x 1080), VGA(720 x 576)	
	Lens	2.8mm	
	Angle of View	H:90° V:80°	
	Day Vision	Color Image, auto switch IR-CUT	
	Nigh Vision	BW Image, 6 Infrared LED	
Audio	Audio Input	Omnidirectional Mic	
	Audio Output	Built-in Speaker	
	Bidirectional Talk	Dual-way bidirectional talk	
	Audio Compression	AMR	
Display	Seven-segment display	5 digits	
Storage	SD Card Type	Micro SD Card slot	
	SD Capacity	Maximum 128 GB	
Network	Ethernet	10/100Mbps (PoE optional)	
	Mobile network	4G LTE/3G/GSM	
Call	Video Call	Android and iOS APP	
	Voice Call	Mobile voice call	
Door Release	Unlock door	Remotely by APP, voice call DTMF, Pin code, Mifare card	
	Relay Outputs	2	
	Exit Button input	1	
	Detector input	1	
	Relay type	NO & NC	
	Relay time	1~7 second	
	Relay load	120VAC/24VDC/10A	
Operation Mode	Keypad	Mechanical Button	
	Reader	Type A Mifare Card	
Alarm	Face detection	Record 10s video clip	
	Notification	Alarm , Warning , Notification	
Power	Power Supply	DC 12V-18V 1A	
	Power Consumption	10 Watts (Max.)	
Environment	Operating Temperature	-10 to +50 °C (+14 to +124 °F)	
	Operating Humidity	10∼80%RH	
	Storage Temperature	-20°C ~ 60° (-4°F ~ 140°F)	
	Storage Humidity	0%~90%	
General	Reset	Reset button	
	SIM Card	Micro SIM Card slot	
	Material	Aluminum	
	Waterproof	IP54	
	Product Dimension	276(L)*116(W)*50(H) mm	
	Net Weight	2.5Kg	



# **PMS** (Property Management Services):

PMS	Subscription	Company Mgnt.
Property Console	User Mgnt.	Company Info.
Property Mgnt.	Alam system	Service Info.
Access Control	Maintenance	System Configure
Security Device	Application	System log
Fire System	User Log	
Tenants		
Visitor Mgnt.		1

# **ASM (Additional Service Module):**

# Notification Cloud Storage Video mgnt Message record Phone call Call record Cloud Storage Video mgnt Face database

