

# WV602-PLUS

Seismic Detector for ATMs and Night Safe Deposit Boxes



## OVERVIEW

The WV602 seismic detector is designed to detect attempts to break into night deposit boxes, automatic teller machines (ATM's) and other reinforced physical areas such as data storage's and filing cabinets. This seismic detector reacts to the characteristic vibration patterns of all breaking-and-entering tools, such as hammers, drills, diamond saws, hydraulic pressure tools and thermal tools like welding torch and thermal lance. It will sense vibrations that occur within a 3 to 14 meter radius of where it is mounted, depending on the material and design of the protected object.

At the same time this detector will allow for normal human activity around the protected area without the risk of creating unwanted alarms. To achieve this high level of accuracy, the detector features "three detectors in one". All three channels (counting, integration, and explosion) analyse the signal frequencies, duration and amplitude, in order to differentiate between random environmental disturbances and real intruder attack. The end result is detectors with excellent detection and false alarm immunity.

The WV600 Plus series provides two different test functions: automatic or manual activated. You can choose between internal test of the detector electronics or, by using the test transmitter VT705P, do a functional test of the detector and its physical contact to the protected object. A complete range of accessories is provided for all kinds of applications to achieve the highest security.

## FEATURES

- Detects all known methods of attacks
- Advanced signal processing differentiates between ambient noise and real attacks
- Extremely low current draw
- Two options of testing
- Adjustable sensitivity
- Full-scale tamper protection
- Complete line of accessories
- Easy to install

# VV602-PLUS

## Seismic Detector for ATMs and Night Safe Deposit Boxes

National Sales Enquiries  
10 Ferntree Place  
Notting Hill, Victoria 3168  
Phone: 1300 361 479  
Outside Australia: +61 3 9239 1200  
[www.fireandsecurityproducts.com.au](http://www.fireandsecurityproducts.com.au)

### SPECIFICATIONS

Input power	9 to 15 VDC 2 V pk-pk
Current consumption	Nominal 8.6 mA
Alarm output	Form A solid state relay, max series resistance 35 ohm
Alarm indication	LED-indication screw no.3
Sensitivity adjustment	5 steps of approx. 6dB each
Test output	Screw no. 4 measuring ambient noise level
Detection range	3 to 14 mm radius. See Installation Manual for planning purposes
Tamper protection	Temperature 84°C, drill shield, opening contact, pry-off contact
Low voltage alarm	7.5 V
IP Rating	IP30
Operating temperature	-20 to + 55°C
Relative humidity	90% at 30°C
Dimensions (W x H x D)	81 x 101 x 28 mm
Colour	Grey, RAL 7035
Weight	380 g

### ORDERING INFORMATION

VV602-PLUS	Dual Detector with 18 curtains of 20 m NC Relay
------------	---



Specifications subject to change without notice.  
Carrier Fire & Security Australia Pty Ltd.  
© 2023 Carrier. All rights reserved. All trademarks are the property of their respective owners.



VV602PLUS\_DS\_FEB23