ICP-CP500ALW Area Addressable LCD Codepad

www.boschsecurity.com





The ICP-CP500ALW is an eight-zone LCD codepad that is compatible with certain Solution Series control panels. Easy to recognize icons display system conditions in a simple to view format. Zone status is indicated numerically across the top of the screen. The codepad notifies you when a zone is unsealed, when there has been an alarm, and in which zone the alarm has occurred.

Also included are a number of single button functions that allow a user to perform various system operations by simply holding down a button for 2 sec. For example, holding the [#AWAY] key arms the system, holding the [1] key tests the sirens, and holding the [3] key tests the strobe lights.

Functions

Arming Methods

You can arm the system by entering your User code and pressing the [#AWAY] key, or quick arm the system by holding down the [#AWAY] key for 2 sec.

- Single button arming of alarm system
- Fire, medical and panic alarms
- Stylish and modern design
- Easy to use
- Backlit buttons for illuminated operation during day or night

Fire, Medical and Panic Alarms

If programmed to do so, simultaneously pressing the outside buttons of a row on any codepad triggers an audible alarm, and an alarm report is sent to the control panel. Press [4] and [6] simultaneously for a fire alarm; press [7] and [9] simultaneously for a medical alarm; and press [1] and [3] or [*STAY] and [#AWAY] simultaneously for a panic alarm.

Certifications and approvals

The ICP-CP500ALW has been tested to the following standards:

Region	Standards	
Australia	A-tick	
New Zealand	Tele-permit	PTC-200
Europe	CE	EMC: EN 55022, EN 55024 Safety: EN 60950 Telecom: TBR21 Environment: EN 50130-4, EN 61000-3-2, EN 61000-3-3

Region	Certification	
Europe	CE	2004/108/EC EMC Directive (EMC); 2006/95/EC Low-voltage Directive (LVD) [ICP-CP500PW][ICP-CP508W] [ICP-CP508LW][ICP-CP516LW][ICP- CP516W][ICP-CP500AW]ICP- CP500ALW]

Installation/configuration notes

Compatibility Information Control Panels

ICP-CC404P, ICP-CC408-CHI, ICP-CC408-APR, ICP-CC408P, ICP-CC408P-ES, ICP-CC488-CHI, ICP-CC488-APR, ICP-CC488P, ICP-CC488P-ES, CC408, CC488, and CC880

Mounting Considerations

The ICP-CP500ALW can be surface mounted indoors using two to four screws.

Parts included		
Quant. 1	Component Codepad	
Technical specifications		
Enclosure Design		
Dimensions:		7.2 cm x 12.7 cm x 2.3 cm (2.8 in. x 5 in. x 1 in.)

Environmental Considerations

Storage Temperature:	+0°C to +50°C (+32°F to 122°F)
Relative Humidity:	20% to 90% (non-condensing)

Power Requirements

Operating Voltage:	11 VDC to 14VDC
Current Draw:	50 mA (maximum)
Radio Frequency Interference (RFI) Immunity:	Complies with AS/NZS3548

Ordering information

ICP-CP500ALW Area Addressable LCD Codepad Eight-zone LCD codepad with easy to recognize system-condition icons and numerically- indicated zone status Order number ICP-CP500ALW

Represented by:

Americas:

Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

Robert Bosch (SEA) Pte Ltd, Security Systems 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 emea.securitysystems@bosch.com www.boschsecurity.com Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

Asia-Pacific:

© Bosch Security Systems 2013 | Data subject to change without notice 2529522827 | en, V1, 01. Oct 2013

China:

Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 latam.boschsecurity@bosch.com www.boschsecurity.com