



Quality Credentials at an affordable Price

General Specifications

Power Requirement	- VDC	Passive (no battery)
Operating Frequency	- MHz	13.56MHZ
Technology	- ISO	ISO 14443A
Size Standard	- ISO	N/A
Material	- Type	ABS
Dimensions	<ul style="list-style-type: none"> - Length (± 0.05mm) - Width (± 0.05mm) - Thickness (± 0.05mm) 	<ul style="list-style-type: none"> 51mm, 2.01" 31.5mm, 1.24" 5.3mm, 0.21"
Colour	- Type: Pantone	Blue
Operating Temperature	<ul style="list-style-type: none"> - Metric - USA 	<ul style="list-style-type: none"> -10°C ~ to +50°C +14°F ~ to +122°F
Relative Humidity	- % max	90%, operating non condensing
IC	- Type	MF3 IC D41
Printing	<ul style="list-style-type: none"> - Sides - Type 	<ul style="list-style-type: none"> N/A N/A
Warranty	- Period	12 Months

DESFire EV1 4K FOB

As BQT Solutions source large quantities of smart credentials, we are able to offer quality, tested credentials at very competitive pricing. We can supply any quantity of credentials either as stock items or on very short lead times. Standard credentials or the custom options (below) are available, contact your BQT Solutions office for pricing and service.

Custom Options:-

- Printing of customer artwork, logos or other information.
- Encoding for Mifare classic.
- Coloured Keyfobs
- Other sizes and styles available