

S-SERIES - FLOOR MOUNT RACKS

Our "S-Series" range of CABAC 19" Floor Mount Racks cater for effortless installation of both the cabinet and your valuable equipment while maintaining and accessing equipment is also made easy with CABAC's wide range of accessories.

Featuring a sturdy frame manufactured to precise dimensions from SPCC high quality cold rolled steel with a thickness of 2mm for the rails, 1.2mm for the frame and 1.0mm side panels, making CABAC's "S-Series" racks light without compromising on strength.



SIDE VIEW



FRONT VIEW



BACK VIEW

CONSTRUCTION

- Sturdy frame made from high quality cold rolled steel
- Rails 2mm, Fame and doors 1.2mm, side panels 1mm
- Colour - Black RAL 9005

GLASS DOOR

- Fully tempered glass 5mm
- Clear view of inside cabinet
- Earth lead connected to door
- Quick release hinges
- Perforated doors available as optional item

REAR BI-FOLD DOORS

- Perforated for increased airflow
- Bi-fold doors save space when opening
- Earth leads connected
- Quick release hinges

SIDE PANELS

- Removable side panels
- Keyed cam locks included

SPECIFICATIONS

PART NO.	DIMENSIONS (mm)					INCLUDED ACCESSORIES			
	RU	Weight (kg)	Width	Depth	Height	Fixed Shelves	Fans	6 Way PDU (10A)	Cage Nuts
CABR18RU6-S	18	50	600	600	988	2	2	1	40
CABR24RU6-S	24	58	600	600	1255	2	2	1	40
CABR24RU9-S	24	66	600	900	1255	2	4	1	40
CABR24RU1-S	24	71	600	1000	1255	2	4	1	40
CABR32RU6-S	32	72	600	600	1610	2	2	1	40
CABR32RU8-S	32	85	600	800	1610	2	4	1	40
CABR32RU1-S	32	85	600	1000	1610	2	4	1	40
CABR42RU6-S	42	86	600	600	2055	3	2	1	40
CABR42RU8-S	42	102	600	800	2055	3	4	1	40
CABR42RU9-S	42	110	600	900	2055	3	4	1	40
CABR42RU1-S	42	117	600	1000	2055	3	4	1	40
CABR42RU1W8-S	42	142	800	1000	2055	3	4	1	40
CABR42RU1200W8-S	42	170	800	1200	2055	3	4	1	40

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

RAIL

- RU marking printed on the front and rear rails for easy placement of components
- **Max load 800kg**
- Easy to adjust rails
- Numerous accessories available for rail mounting

CABLE ACCESS

- Generous cable access on top (front and rear)
- Bottom cable access via 5 removable cable entry plates

AIR FLOW

- Fan box included with all floor mount racks
- 600mm deep racks - 2 fans
- 800mm and deeper racks - 4 fans
- Fan box mounted on inside top rack

PDU

- 6-way 10A horizontal rail mounted
- Australian 3 pin plug and sockets
- PDU range available as optional extra

CABLE MANAGEMENT

- 120mm between front door and rail for cable management
- Horizontal cable management accessories available
- Vertical cable management accessories available
- **800mm wide racks feature built in vertical cable management**

PALLET MOUNTING

- Secured to and shipped on a pallet for safe and easy transportation
- Attached to pallet via brackets - quick and easy to remove once on-site

FLOOR MOUNTING

- Four heavy duty castors (2 with brackets) fitted for positioning rack on site
- Four adjustable levelling feet

SHELF ACCESSORIES

- Cantilever trays
- Fixed shelves
- Sliding shelves
- Storage drawer

S-SERIES - FLOOR MOUNT RACKS

ACCESSORIES: SHELVES

The CABAC range of shelving accessories for our 19" Racks are designed to offer solutions for most requirements and cover many shelf types for floor mounted cabinets of various depths. Some items are suitable for wall mount & swing frame racks.



NO.	PART NO.	DESCRIPTION	SUITS RACK		DEPTH	WIDTH	RU SPACE	MOUNTING	WEIGHT KG	MAX LOAD KG
			TYPE	DEPTH						
1	CABRCS300-S	CABAC Cantilever Shelf 483 x 300 x 43	ALL	ALL	300	483	1	RU Rail	2.5	20
	CABRCS350-S	CABAC Cantilever Shelf 483 x 350 x 43	ALL	ALL	350	483	1	RU Rail	3	20
2	CABRCS400-S	CABAC Cantilever Shelf 483 x 400 x 43	ALL	600 to 1000	400	483	1	RU Rail	3.5	20
	CABRCS300	Cantilever Shelf 19" RM 300mm Black	ALL	ALL	300	485	2	RU Rail	2.5	30
3	CABRCS400	Cantilever Shelf 19" RM 400mm Black	ALL	600 to 1000	400	485	2	RU Rail	3.2	30
	CABRFT350-S	CABAC Fixed Shelf 470 x 350 x 48	FM	600	350	470	0	Side Rail	2	90
4	CABRFT550-S	CABAC Fixed Shelf 470 x 550 x 48	FM	800	550	470	0	Side Rail	3	90
	CABRFT650-S	CABAC Fixed Shelf 470 x 650 x 48	FM	900	650	470	0	Side Rail	3.2	90
4	CABRSS350-S	CABAC Sliding Shelf 470 x 350 x 53	FM	600	350	470	1	RU Rail	2.26	30
	CABRSS550-S	CABAC Sliding Shelf 470 x 550 x 53	FM	800	550	470	1	RU Rail	3.26	30
	CABRSS650-S	CABAC Sliding Shelf 470 x 650 x 53	FM	900	650	470	1	RU Rail	4.26	30
	CABRSS750-S	CABAC Sliding Shelf 470 x 750 x 53	FM	1000	750	470	1	RU Rail	7	30

KEY	WM	Wall mount
	SF	Swing Frame
	FM	Floor Mount

ACCESSORIES: PERFORATED FRONT DOORS

CABAC offers, in addition to the standard door supplied with our floor mounted cabinets, a range of perforated doors for applications where increased airflow is required. Airflow is improved using perforated doors and effective fan configurations to achieve maximum heat dispersion. The perforations in the door are uniformly punched into cold rolled steel. These doors are supplied for retro fitting to the CABAC range and are sized according to height measured in RU and width.

PART NO.	DESCRIPTION	WEIGHT (KG)	SUITS RACK
CABRPF18-S	19" RU18 Front Door Perforated	6	18RU x 600 Wide
CABRPF24-S	19" RU24 Front Door Perforated	8	24RU x 600 Wide
CABRPF32-S	19" RU32 Front Door Perforated	10	32RU x 600 Wide
CABRPF42-S	19" RU42 Front Door Perforated	12	42RU x 600 Wide
CABRPF42W8-S	19" RU42 Front Door Perforated	14	42RU x 800 Wide



In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.