



garland
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MCP321LG

Description 1 Pair, Stranded 18 AWG PACW, Twisted, PE Insulation, 4V-75 PVC Sheath.

Applicable Standards AS/NZS 1125, AS/NZS 3808


Suitable Applications Used to make the electrical connection between loudspeakers and audio amplifiers.

*Not intended for direct connection to mains power.

Cable Construction Drawing



Cable Construction Relative Parts



Cable Description

Conductor	AWG	Area (mm ²)	Stranding	Diameter (mm)	Material
	18	1.0	32/0.2	1.31	PACW
Insulation	Pairs :		1		
	Material :		PE		
	Colour :		Red, Black		
	Nominal Thickness (mm) :		0.45		
	Nominal OD (mm) :		2.3		

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.garlandcables.com.au

MCP321LG-160519v2





garland
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Sheath	Material :	4V-75 PVC
	Colour :	Light Green
	Nominal Thickness (mm) :	1.0
	Nominal OD (mm) :	6.6

Electrical Properties

Max. Conductor DC Resistance @ 20°C	19.5Ω/km
Voltage Test: Conductor to core	1.0 kV ac/1min

Mechanical Properties

Operating Temperature Range	-15 to 90°C
Max. Recommended Pulling Tension	140N
Min. Bend Radius (install)	66mm
Approximate Mass	5.1kg/100m

Supply Information

Part Number	Pack Size	Pack Type	Dimensions	Qty Per Carton
MCP321LG500	500m	Wooden Reel	W44 x H21.8cm	1R
MCP321LG250	250m	TBA	TBA	TBA

- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.garlandcables.com.au

MCP321LG-160519v2

made by

madison