


## RADUM 2 PAIR 7/0.25 INDIVIDUAL SCREENED LSZH CABLE

CONSTRUCTION		
Type	2 Pair 7/0.25 Individual Screened LSZH Cable	
Conductor	Stranded 22 AWG 7 Strands x 0.25mm Tinned Copper	
Insulation	0.26mm LS0H Compound	
1st Pair	Red & Black	
2nd Pair Colours	White & Green	
Pair Shielding	Individual Aluminium Polyester Laminate Tape	
Construction	Pairs cabled on common axis to reduce diameter	
Drain Wire	7 strands x 0.25mm Tinned Copper	
Jacket	LS0H Compound	
Jacket Colour	Green	
Jacket O/D	4.27mm	
Impedance	45 Ohm	
Insulation Resistance	100 mega ohms between shields	
Working Voltage	50 Volts between adjacent shields	
Printing	Black Printing on the Green Sheath Printing to be repeated at approximately 0.05m intervals WWW.RADUM.COM.AU RADUM 2P INDI SCREENED LS0H CABLE N11251	
Shipping Mark	RADUM in a triangle 	
Packing	Note: The Diameter of the Centre hole in the drum MUST be at least 30mm or the shipment will be rejected 100m Drum (4 by 100m drum per cardboard box) 500m Drum (1 by 500m drum per cardboard box)	
Labelling	<b>On the outside of each drum flange</b>	
	<b>On the 100m Drum</b> BCLSP27025-100 RADUM 2 Pair Individual Screened LSZH Cable N11251 Length - 100m	<b>On the 500m Drum</b> BCLSP27025-500 RADUM 2 Pair Individual Screened LSZH Cable N11251 Length - 500m
	<b>On the outside of each packing box</b>	
	<b>On the 100m Drum</b> BCP27025-500 RADUM 2 Pair Individual Screened LSZH Cable N11251 Quantity: 4 x 100m	<b>On the 500m Drum</b> BCP27025-500 RADUM 2 Pair Individual Screened LSZH Cable N11251 Quantity: 1 x 500m