

PRODUCT **DATASHEET**

0-

6 WAY INDIVIDUAL SWITCH POWERBOARD

This high quality INDIVIDUALLY switched 6 way powerboard is suited to domestic and commercial applications. This quality designed and manufactured unit also provides surge and overload protection to downstream appliances. Typically devices protected include audio, video, entertainment and computer equipment.

As an added feature it also provides protection from both EMI and RFI (Electromagnetic and Radio interference).

It comes with a convenient 2m long power lead with a right angle power plug. The right angle plug, requiring less space, can easily and neatly fit behind furniture.

FEATURES

- · Six Australian power outlets
- · Each power outlet has an individual switch
- Surge and overload protection
- · EMI and RFI protection
- 2m power lead with right angle plug

PB6SW

TECHNICAL SPECIFICATIONS

Part No.	PB6SW
Voltage Rating	230-240Va.c. 50Hz
Current Rating	10 Amp max.
Power Rating	2400 Watt max.
Surge Current	4500A
Surge Protection	Yes
Response Time	Less than 20 nano seconds
Clamping Voltage	Less than 275V
Energy Absorption	525 Joules
Power Cord Length	2m
Plug	Right angle



Blister Packed Powerboard

CABAC has a policy of continuous product improvement and reserves the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where available, technical and MSDS data sheets are available on the CABAC website. All CABAC products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to CABAC website for terms and conditions on warranty. The one day, one call, one delivery does not cover the following items: Cabchem, Cast Resin kits, Custom manufacturing & kitting, Cabinets, Ladders, Pits & Pillars, CABTRAY & Branch stock orders.



Ph: 133 122