

CATEGORY 6 REDUCED DIAMETER PATCH CORDS

Category 6 reduced diameter patch leads are ideal for high density patching as their small 3.6mm diameter jacket requires less space in a rack than standard Category 6 patch leads. As racks become more heavily populated with equipment, cables and patch cords and as space inside a rack fills, cable management becomes more and more of a challenge with large bundles of cable that reduce air flow and are difficult to neatly route between switches and patch panels.

FEATURES & BENEFITS

- Reduced diameter for improved flexibility and higher density patching
- Smaller bend radius from 28 AWG stranded conductors
- Performance tested to ANSI/TIA 568-C.2
- Available in a variety of lengths starting from 0.3m



STANDARD COMPLIANCE

- RCM AS/CA S008
- ANSI/TIA-568-C.2
- RoHS
- AS/NZS 11801
- ANSI/TIA-568.2-D

SPECIFICATIONS

Number of Pairs	4
Conductors	28 AWG (7/0.12) Stranded Bare Copper
Jacket Material	LSZH
Outer Diameter	3.6mm (+/- 0.2mm) nominal
Connector Type	RJ45 Plug (8P8C)
Wiring Scheme	568A
Operating Temperature	-10 to +60

ORDERING INFORMATION

LENGTH	0.3	0.5	1	1.5	2	3	5
Black	PLC6BK0.3SL	PLC6BK0.5SL	PLC6BK1SL	PLC6BK1.5SL	PLC6BK2SL	PLC6BK3SL	PLC6BK5SL
Blue	PLC6BL0.3SL	PLC6BL0.5SL	PLC6BL1SL	PLC6BL1.5SL	PLC6BL2SL	PLC6BL3SL	PLC6BL5SL
Green	PLC6GN0.3SL	PLC6GN0.5SL	PLC6GN1SL	PLC6GN1.5SL	PLC6GN2SL	PLC6GN3SL	PLC6GN5SL
Red	PLC6RD0.3SL	PLC6RD0.5SL	PLC6RD1SL	PLC6RD1.5SL	PLC6RD2SL	PLC6RD3SL	PLC6RD5SL
White	PLC6WH0.3SL	PLC6WH0.5SL	PLC6WH1SL	PLC6WH1.5SL	PLC6WH2SL	PLC6WH3SL	PLC6WH5SL
Yellow	PLC6YL0.3SL	PLC6YL0.5SL	PLC6YL1SL	PLC6YL1.5SL	PLC6YL2SL	PLC6YL3SL	PLC6YL5SL

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.