RADUM PTY LTD

RADUM 2 x 26/0.30 FIGURE 8 CABLE

CONSTRUCTION	
Type	2 x 26/0.30mm Figure 8 Cable
Construction	Parallel Webbed 26/0.30mm
Nominal Area	1.8 square mm
Amp Rating	18 Amps
Insulation Thickness	0.3mm
Nominal O/D	4.0 x 7.0 mm
Copper Conductor Sheath	V75 PVC
Colours and Trace	Red/Black

Printing	Printing to be repeated at approximately 0.05m intervals WWW.RADUM.COM.AU RADUM 2 x 26/0.30 F8 CABLE N11251
Shipping Mark	RADUM in a triangle RADUM
Packing	Note: Plastic spools MUST be RADUM standard type 100m Drum (4 by 100m drum per cardboard box) 250m Drum (2 by 250m drum per cardboard box) 500m Drum (1 by 500m drum per cardboard box)
Labelling	**On the outside of each 100m / 250m / 500m drum flange**
	BCAC1026-XXX RADUM F8 26/0.30 Red/Black H/Duty N11251 Length - XXXm
	On the outside of each packing box
	BCAC1026-XXX RADUM F8 26/0.30 Red/Black H/Duty N11251 Quantity: X x XXXm