
Part No: MCP2IS-W

Description	7/0.25mm (22 AWG) TACW, PP Insulated, 2 Pair, Individual Al- Polyester Laminate Screened with a shared Drain Wire, Overall PVC Sheath
Applicable Standards	AS/CA S-008, AS 1125, AS 1049, UL 444
Suitable Applications	For the interconnection of instruments and control equipment. Also used in audio applications as a microphone or line level cable and in low bit rate data applications such as RS-232 to connect DTE equipment together. Can be used for security systems to connect sensors, touch pads and keypads to central units/monitors.

Cable Construction Drawing

Cable Construction Relative Parts







Cable Description						
Conductor	No. of Strands	Nominal Strand Size	Material			
	7	0.25 mm	TACW			

With Garland, you are always well connected.





Industrial / Power / Data / Security / Fibre

	Pairs:		2	2		
Insulation	Material:		Polypropyle	Polypropylene		
	Colours:			Pair 1: Red & Black Pair 2: Green & White		
	Diameter:		1.2 mm	1.2 mm		
	Average Thickness:		0.25 mm	0.25 mm		
Cabling	Cabling Direction: Left Har		Left Hand, LH or "S" d	d, LH or "S" direction.		
	Cabling Lay: ≤ 100 mr		≤ 100 mm	n		
Screening Tape	Po ou		Individually screened with 2 x Aluminium-Polyester Laminate Tapes. Aluminium facing out and in contact with a single drain wire.			
	Minimum Overlap: 20%			I		
Drain Wire	No of Strand	S	Nominal Strand Size	Material		
	7		0.2 mm	TACW		
Sheath	Material: 4V-75 PVC					
	Colour:		Grey	Grey		
on out	Diameter:		4.3	4.3		
	Average Thickness:		0.5 mm			
Electrical Properties						
Conductor DCR (22 AWG conductors) \leq 57.4 Ω /km @ 20°C (UL 444)						
Mechanical Properties						
Operating Temperature Range		-15 to	75℃			
Max. Recommended Pulling Tension		96N				
Min. Bend Radius (install)		45mm	1			
Approximate Mass		2.9 kg	J/100m			

With Garland, you are always well connected.





Industrial / Power / Data / Security / Fibre

Supply Information							
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet			
100m	Plastic Reel	F22 x W7 cm	6R	32			
300m	Pull Box	-	1	45			
500m	Composite Reel	F32 x W19 cm	1	36			

Madison reserves the right to make changes to the products described in this specification without prior notice



All values subject to factory tolerances