


RADUM 2 x 24/0.20mm LSZH FIGURE 8 CABLE



CONSTRUCTION	
Type	2 x 24/0.20mm LSZH Figure 8 Cable
Construction	Parallel Webbed 24/0.20mm
Copper Conductors	24 Strands 0.20mm
Nominal Area	0.75 square mm
Amp Rating	7.5 Amps
Insulation Thickness	0.3mm
Nominal O/D	2.40 x 5.40 mm
Copper Conductor Sheath	LS0H Compound
Colours and Trace	Green/White
Construction	Overall Sheath MUST not stick to conductors

Printing	Printing to be repeated at approximately 0.05m intervals WWW.RADUM.COM.AU RADUM LS0H 2/0.20 F8 CABLE N11251
Shipping Mark	RADUM in a triangle 
Packing	Note: Plastic spools MUST be RADUM standard type or the shipment will be rejected 100m Drum (4 by 100m drum per cardboard box) 250m Drum (2 by 250m drum per cardboard box) 500m Drum (1 by 500m drum per cardboard box)
Labelling	On the outside of each 100m / 250m / 500m drum flange
	BCLSF82402-XXX RADUM F8 - 24/0.20 LSZH Green/White N11251 Length - XXXm
	On the outside of each packing box
	BCLSF82402-XXX RADUM F8 - 24/0.20 LSZH Green/White N11251 Quantity: X x XXXm