


## RADUM 6 CORE 14/0.20 J/F SECURITY CABLE

### DESCRIPTION:

Radum Jelly Filled Security Cable is used for the interconnection of data terminal and communication equipment. It is designed for underground applications, and suitable for direct burial.

CONSTRUCTION	
Type	6 Core 14/0.20 Jelly Filled Security Cable
Conductor	Stranded 21 AWG 14 Strands x 0.20mm Bare Copper
Insulation	Cores: 6
	Material: Polypropylene
	Colour: White/Blue, Red/Black, Yellow/Green
	Nominal Thickness: 0.3mm
Filler	Nominal OD: 1.5mm
	Jelly Filled
Sheath	Material: Polyester Tape
	Coverage: 100%
	Material: Polyethelene
	Colour: Black
Voltage Rating	Nominal Thickness: 0.6mm
	Nominal OD: 6.5mm
Max. Conductor DC Resistance	ELV
Min. Insulation Resistance	45.2 $\Omega$ /km @ 20°C
Operating Temperature Range	1000m $\Omega$ /km @ 20°C
Max. Recommended Pulling Tension	-30 to 70°C
Min. Bend Radius	166N
	65mm



<b>Printing</b>	White Printing on the Black Sheath Printing to be repeated at approximately 0.05m intervals WWW.RADUM.COM.AU RADUM 6 CORE 14/0.20mm J/F SECURITY CABLE N11251	
<b>Shipping Mark</b>	RADUM in a triangle 	
<b>Labelling</b>	<b>On the outside of each drum flange</b>	
	<b>On the 300m Drum</b> BCUGS61402-300 300Mtr 6 Core 14/0.20 Outdoor J/F Cable Length - 300m	<b>On the 500m Drum</b> BCUGS61402-500 500Mtr 6 Core 14/0.20 Outdoor J/F Cable Length - 500m
	<b>On the outside of each packing box</b>	
	<b>On the 300m Drum</b> BCUGS61402-300 300Mtr 6 Core 14/0.20 Outdoor J/F Cable N11251 Quantity: 1 x 300m	<b>On the 500m Drum</b> BCUGS61402-500 500Mtr 6 Core 14/0.20 Outdoor J/F Cable N11251 Quantity: 1 x 500m