

# DHI-ASR2101A-D

Access Reader



### **Series Overview**

As a key part of the access control system, the DHI-ASR2101A-D access control card reader supports card and password unlock, and sends the information to the access controller for verification. With a thin and elegant design, it is applicable to industrial zones, office buildings, schools, factories, stadiums, CBD, residential area, government properties, etc.

## **Technical Specification**

| К          | 2 | C | 11 |
|------------|---|---|----|
| $^{\circ}$ | а | 0 | ı۷ |

| Product Type | Card reader      |
|--------------|------------------|
| Buzzer       | Yes              |
| Casing       | PC/acrylic panel |

#### Function

| Unlock Mode | Card swiping/password<br>Multiple unlocking modes |
|-------------|---|
| Card Type   | ID card   |

#### Performance

| Response Time         | 0.1 s                |
|-----------------------|----------------------|
| Card Reading Distance | 0 cm-3 cm (0"-1.18") |

#### Port

| RS-485       | 1 channel        |
|--------------|------------------|
| Wiegand      | 1 output channel |
| Alarm        |                  |
| Tampar Alarm | Voc              |

- PC material, acrylic panel and IP66, suitable for indoor and outdoor use.
- · Support contactless recognition of ID card.
- · Support card/password unlock.
- Support communication through RS-485 and Wiegand 34 (Wiegand 26 can be configured).
- Support buzzer and indicator prompt.
- · Support anti-tampering alarm.
- The built-in watchdog can detect and control abnormal operation status of the equipment and perform recovery processing to ensure the long-term operation of the equipment.
- All connection ports have overcurrent and overvoltage protection.











#### General

| Power Supply          | 12V 0.5A DC  |
|-----------------------|--|
| Protection            | IP66 (silicon sealant is needed, see the manual)   |
| Power Consumption     | Standby ≤ 0.9W, working ≤ 1.7W   |
| Product Dimensions    | 123 mm × 86 mm × 15 mm (4.84" × 3.38" × 0.59") (L × W × H)   |
| Packaging Dimensions  | 185 mm × 163 mm × 71 mm (7.28" × 6.41 × 2.80")<br>(L × W × H, 1 in inner carton)<br>578 mm × 383 mm × 349 mm (22.76" × 15.08" × 13.74")<br>(L × W × H, carton) |
| Operating Temperature | -30°C to +70°C (-22°F to +158°F)   |
| Operating Humidity    | 5%RH–95% (non-condensing)  |
| Operating Environment | Indoor; outdoor  |
| Gross Weight          | 0.35 kg (0.77 lb)  |
| Installation          | Surface mount  |
| Certifications        | CE; FCC  |
|                       |  |

| Ordering Information |                |  |
|----------------------|----------------|--|
| Туре                 | Model          | Description  |
| Access<br>Reader     | DHI-ASR2101A-D | DHI-ASR2101A-D Outdoor<br>Waterproof Password ID Card Reader |

## Dimensions (mm[inch])





## Application

