

DHI-ARD323-W2-B

Dahua Wireless Door Detector (Black)



- · Signal strength detection;
- · Low battery alarm;
- · temperature monitoring;
- Frequency hopping function and two-way communication technology ensure communication stability;
- · Cloud update and automatic recovery from update failure.

Series Overview

The Wireless Door Detector leverages the magneto-switch principle of reed tubes to quickly recognize and send messages through the hub to you when the doors and windows of a building are being broken into. The detector also sends notifications when it detects an intrusion. Easy to install, it can be attached to doors and windows that need protection.

Technical Specification			
$1 \times \text{green alarm indicator}$			
$1 \times power button$			
Cloud update			
Yes			
Yes			
–15 °C to +65 °C (+5 °F to +149 °F) (indoor)			
Reed switch			
< 40 mm (1.57")			
Yes			
Non-metal doors			
433.1 MHz–434.6 MHz			
Limit 10 mW			
Two-way			

Communication Distance Encryption Mode AES128 Frequency Hopping Yes General Power Supply Power Supply Type Battery Life 4 years (The external input type is NO) 2 years (The external input type is NC or Pulse) Low Battery Threshold 2.7V Battery Restore Threshold 2.8V Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity Net Weight 70 g (0.15 lb) Gross Weight Installation Bracket mount Casing Material CE Anti-corrosion Level Storage Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor)		
Frequency Hopping General Power Supply CR123A battery Power Supply Type Type C Battery Life 4 years (The external input type is NO) 2 years (The external input type is NC or Pulse) Low Battery Threshold 2.7V Battery Restore Threshold Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%-90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Communication Distance	Up to 1,200 m (3,937.01 ft) in an open space
General Power Supply CR123A battery Power Supply Type Type C Battery Life 4 years (The external input type is NO) 2 years (The external input type is NC or Pulse) Low Battery Threshold 2.7V Battery Restore Threshold 2.8V Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%–90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Encryption Mode	AES128
Power Supply Power Supply Type Type C Battery Life	Frequency Hopping	Yes
Power Supply Type Type C Battery Life 4 years (The external input type is NO) 2 years (The external input type is NC or Pulse) Low Battery Threshold 2.7V Battery Restore Threshold 2.8V Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%-90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	General	
Battery Life 4 years (The external input type is NO) 2 years (The external input type is NC or Pulse) Low Battery Threshold 2.7V Battery Restore Threshold 2.8V Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%–90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Power Supply	CR123A battery
Eattery Life external input type is NC or Pulse) Low Battery Threshold 2.7V Battery Restore Threshold 2.8V Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%-90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Power Supply Type	Type C
Battery Restore Threshold 2.8V Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%-90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Battery Life	
Power Consumption Max. 70 mW Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%–90% (RH) Product Dimensions (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Max. 70 mW 10%–90% (RH) 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Product Dimensions 10%–90% (RH) 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Possible Temperature 10%–90% (RH) 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Bracket mount Casing Material PC + ABS	Low Battery Threshold	2.7V
Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) (indoor) Operating Humidity 10%–90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Battery Restore Threshold	2.8V
Operating Humidity 10%–90% (RH) Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Power Consumption	Max. 70 mW
Product Dimensions 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Operating Temperature	$-10~^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +131 $^{\circ}\text{F})$ (indoor)
Net Weight 70 g (0.15 lb) Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Operating Humidity	10%-90% (RH)
Gross Weight 115 g (0.25 lb) Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Product Dimensions	100.2 mm \times 20.8 mm \times 20.3 mm (3.94" \times 0.82" \times 0.80") (L \times W \times H)
Installation Bracket mount Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Net Weight	70 g (0.15 lb)
Casing Material PC + ABS Certifications CE Anti-corrosion Level Basic Protection	Gross Weight	115 g (0.25 lb)
Certifications CE Anti-corrosion Level Basic Protection	Installation	Bracket mount
Anti-corrosion Level Basic Protection	Casing Material	PC + ABS
	Certifications	CE
Storage Temperature $-10~^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +131 $^{\circ}\text{F}$) (indoor)	Anti-corrosion Level	Basic Protection
	Storage Temperature	$-10~^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +131 $^{\circ}\text{F})$ (indoor)
Storage Humidity 10%–90% (RH)	Storage Humidity	10%-90% (RH)
Packaging Dimensions $ \begin{array}{l} 135.0~\text{mm}\times 98.5~\text{mm}\times 27.8~\text{mm}~(5.31"\times 3.88"\times 1.09") \\ (\text{L}\times \text{W}\times \text{H}) \end{array} $	Packaging Dimensions	135.0 mm × 98.5 mm × 27.8 mm (5.31" × 3.88" × 1.09") (L × W × H)

Wireless Door Detector | DHI-ARD323-W2-B


Ordering Information

Туре	Model	Description
Wireless Door Detector	DHI-ARD323-W2-B	Dahua Wireless Door Detector (Black)

Installation



Dimensions (mm[inch])



Application

