

DHI-ARD323-W2(S)-B

Dahua Wireless Door Detector (Small, Black)



- · Signal strength detection;
- · Low battery alarm;
- · temperature monitoring;
- Frequency hopping function and two-way communication technology ensure communication stability;
- · Cloud update and automatic recovery from update failure.

Series Overview

The Wireless Door Detector leverages the magneto-switch principle of reed tubes to quickly recognize and send messages through the hub to you when the doors and windows of a building are being broken into. The detector also sends notifications when it detects an intrusion. Easy to install, it can be attached to doors and windows that need protection.

Technical Specification			
Function			
Indicator Light	$1 \times \text{green alarm indicator}$		
Button	$1 \times power button$		
Remote Update	Cloud update		
Low Battery Detection	Yes		
Tamper	Yes		
Measuring Range (Temperature)	-15 °C to +65 °C (+5 °F to +149 °F) (indoor)		
Technical			
Sensor	Reed switch		
Movement Distance	< 40 mm (1.57")		
Test Mode	Yes		
Scenario	Non-metal doors		
Wireless			
Carrier Frequency	433.1 MHz–434.6 MHz		
Transmitter Power (EIRP)	Limit 10 mW		
Communication Mechanism	Two-way		


Communication Distance	Up to 1,200 m (3,937.01 ft) in an open space	
Encryption Mode	AES128	
Frequency Hopping	Yes	
General		
Power Supply	CR123A battery	
Power Supply Type	Type C	
Battery Life	4 years (The external input type is NO) 2 years (The external input type is NC or Pulse)	
Low Battery Threshold	2.7V	
Battery Restore Threshold	2.8V	
Power Consumption	Max. 70 mW	
Operating Temperature	$-10~^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +131 $^{\circ}\text{F})$ (indoor)	
Operating Humidity	10%-90% (RH)	
Product Dimensions	100.2 mm \times 20.8 mm \times 20.3 mm (3.94" \times 0.82" \times 0.80") (L \times W \times H)	
Net Weight	70 g (0.15 lb)	
Gross Weight	115 g (0.25 lb)	
Installation	Bracket mount	
Casing Material	PC + ABS	
Certifications	CE	
Anti-corrosion Level	Basic Protection	
Storage Temperature	$-10~^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +131 $^{\circ}\text{F}$) (indoor)	
Storage Humidity	10%-90% (RH)	
Packaging Dimensions	135.0 mm \times 98.5 mm \times 27.8 mm (5.31" \times 3.88" \times 1.09") (L \times W \times H)	

Wireless Door Detector | DHI-ARD323-W2(S)-B


Ordering Information

Туре	Model	Description
Wireless Door Detector	DHI-ARD323-W2(S)-B	Dahua Wireless Door Detector (Small, Black)

Installation



Dimensions (mm[inch])



Application

