

VTO6100C

IP Villa Outdoor Station



Technical Specification	
Model	VTO6100C
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Image Sensor	1/3" 1.3MP CMOS
Lens	3.6mm
Angle of View	D:95° H:75°
Day/Night	Color Image
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Operation Mode	
Keypad	Single Mechanical Button
Reader	Mifare Card
Interface	
Door Control	2(1 relay out for main lock, 1 extended by access control module)
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	-
Network	
Ethernet	10M/100Mbps Self-adaptive

Features

- HD CMOS camera
- · Plastic panel, IP54
- \cdot Night vision & Voice indication
- · Video & Audio messaging
- \cdot Remote intercom with mobile APP
- · Flush mounted















Network Protocol	TCP/IP
General	
Ingress Protection	IP54
Tamper Switch	1
Installation	Flush
Material	Plastic
Power	DC 12V
Power Consumption	Standby ≤1W, Work ≤10W
Working Temperature	-30°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	100.0mm×141.0mm×42.0mm
Weight	0.4Kg

Dimensions View Area





Application



