

# VTH1510CH

IP Indoor Monitor



## Technical Specification

Model	VTH1510CH
-------	-----------

### System

Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS

### Video

Video Compression	H.264
-------------------	-------

### Audio

Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk

### Display

LCD Screen	7" 800x480, Resisitive
------------	------------------------

### Operation Mode

Input	Touch buttons
-------	---------------

### Interface

Alarm In	6
Alarm Out	1
RS485	1

### Network

Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP

### General

Memory Slot	Micro SD, Max 32GB
-------------	--------------------


## Features

- 7" TFT Resistive touch screen
- IPC surveillance
- Alarm integration
- Micro SD card optional, max 32GB
- Record & Snapshot(SD card needed)




Installation	Surface
Power	DC 12V/ supply directly by VTNS1060A
Power Consumption	Standby ≤1.5W, Work ≤7W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	200.5mm×136.5mm×22.0mm
Weight	0.8Kg

Dimensions



View Area



Application

