

TRY series doorstations

The security and piece of mind you need all year round.





The Sentry Doorstation series are powerful all in one, interactive telephone units that thinks for you. They offer security and control literally at your finger tips. Designed to fit any place you require a high quality, loud speaker, hands-free telephone. It is well suited for homes, hotels, hospitals and universities as well as many business and commercial settings. Protecting you against unwanted entry onto your property, this unit will give you the ability to authorise access to welcomed visitors without having to leave the comfort of your home or office. The Sentry, making sure your safety and well-being come first!

options:

There are four models available in the Sentry series, all with their own unique features;

LP this unit is totally telephone line powered and will supply sufficient audio level for low noise environments. **Doorcom** designed for general purpose situations, it features easy programming for quick installation (power pack supplied). this unit features interactive voice prompt for quick and easy programming (power pack supplied).

VoIP using a CAT5E cable to connect to a computer serve which acts as the PBX.

All three models have the same general basic features and casing options. For further details on which model will best accommodate your needs please refer to each respective brochure; Sentry LP, Sentry Doorcom, and Sentry VolP.

This brochure will outline the common physical features of the Sentry doorstations.

keypad:

There are two options available for the Sentry keypad diallers, one is the standard dialler and the other a speed dialler. Both diallers boast a vandal resistant 4x3 metal keypad. A standard dialler will operate similar to a normal hands-free telephone, pressing the '#' key will turn the unit on, then simply dial in the number you wish to call. To end a call or hang up the unit, press the '* key. Alternatively there is the speed dialler, which stores preset numbers in the Sentry and the user simply presses a location number on the keypad to dial the number stored for that preset.




The standard panel size for all Sentry units are 130.0mm x 270.0mm, custom panel sizes and layouts can be tailor made to your needs. Panels are available in either vertical or horizontal, and can be anodised aluminium or stainless steel. If you require the panel to be made of different material (ie. brass, gold-plated, etc), this to is available upon request.



SENTRY series doorstations

auto dialler:

The Sentry auto dialler is a single button doorstation which will dial a preset number once the button is pressed. The duration of how long the button needs to be depressed for before it makes a call can also be set. If the line is engaged or there is no answer the Sentry can be programmed to dial a second destination. If continuous or engaged tone is detected the Sentry will automatically hang up. In the event of noisy environments a *push-to-talk* feature can be implemented in order to overcome the background noise level while on a call. (all models).



The Sentry auto dialler also features an auto-answer option for remote programming purposes. All units have door release as a standard feature. If two different gates/doors need to be remotely opened independently, a second door release relay can be fitted upon request.



multi number dialler:

The Sentry multi number dialler offers similar features to the single button auto dialler. Each button on a multi number dialler can be programmed to have its own unique number. Each button can also have an engraved label next to it to help identify its call destination or a call card can be inserted into the panel so that the call numbers and labels can be changed with ease. When ordering your multi number dialler you can specify exactly how many call buttons you want. The panel size may vary depending on the amount of buttons requested.



Other features of the Sentry doorstations are;

- ⇒ battery backup and solar panel (optional)
- remote programming facilities
- remote operating features
- remote diagnostic testing
- remote relay activation
- self identification



enclosures:

A vast range of enclosures are available specifically for our standard 130.0mm \times 270.0mm sized panels, from stainless steel to powder-coated, weather-shielding to fully enclosed housings and flush mount brackets.



Our enclosures are sure to accommodate all of your needs.

Please refer to the Enclosures brochure for further details.

The information contained on this product brochure is subject to change without notice.







VIC Unit 7, 170 Forster Road, Mt Waverley VIC 3149

NSW Unit 9A, 142 James Ruse Drive, Parramatta NSW 2150

QLD 15-19 Hudson Road, Albion QLD 4010

WA Unit 4, 200 Balcatta Road, Balcatta WA 6021

ACT Unit 2, 157-161 Gladstone Street, Fyshwick ACT 2609