

Activor Wiegand remote - RTW19 and RTW01



RTW19



RTW01

- Wiegand 26 bit; 4 or 2 channels
- Frequency: 433 MHz (other frequencies are available on request)
- Keeloq rolling code: 4.3 billion combination
- SAW resonator (filter) locked (+/- 75KHz); Superhet technology
- Operating Range: 100m (open air)
- Transmitting power: <10mW
- Operating Voltage: 6 V powered by 2 x lithium batteries
- Battery Life: 3 years under normal operating conditions
- Current: <1uA standby; 12mA max.
- Low battery indication
- Auto shutoff: the remote stops transmitting if a button gets pressed for 25s

Activor Wiegand outdoor receiver – RRW-01



- 4-channel standard 26bit Wiegand output
- Frequency: 433MHz
- Voltage: 9-15VDC; Current: 15mA
- Option of pass-through or site-code verification
- Dimensions: L190 x W100 x H45mm
- 4 channels with LED indication
- Outdoor application; IP66

Activor Wiegand indoor receiver – RRW02



- 4-channel standard 26bit Wiegand output
- Frequency: 433MHz
- Voltage: 9-15VDC; Current: 15mA
- Option of pass-through or site-code verification
- 4 channels with LED indication
- Dimensions: 87 x 63 x 27mm