

Secor® Reed Switches

Where quality, price and service ALL count

- World class benchmarked
- OKI reed switch inside
- Crush resistant
- Wider operating gap, more tolerance and less false alarm



WM88 roller shutter door

- Size: Reed switch 106 x 36.5 x 10mm
Magnet 106 x 15.5 x 16mm
Bracket 107 x 50 x 50mm
- Gap 65mm
- Extra wide gap
- 600mm armoured cable (stainless)
- Robust constructed and epoxy sealed - no corrosion
- Universal mounting with L bracket



WSS60 extra wide-gap surface mount

- Size: 90(L) x 13.5(W) x 18.5(H) mm
- Gap: 60mm
- Colour: white, black, beige, brown, grey, green and yellow
- Reed switch epoxy sealed
- Easy to install and solder



WSF46 wide gap press to fit

- Size: 9.5mm(Dia) x 32mm(L)
- Gap: 28mm
- Colour: white and brown



WSS14 mini surface mount

- Size: 33(L) x 7(W) x 13(H) mm
- Gap: 30mm
- Adhesive or screw mount
- Mid lead



WSF47 truly mini

- Size: 9.5mm(Dia) x 15mm(L)
- Gap: 15mm
- Colour: white and brown



WSF41 steel door 19mm

- Size: 19mm(Dia) x 21mm(L)
- Gap: 35mm
- Colour: white and brown



WR32 tamper switch with adjustable plunger

- Size: 15mm(Dia) x 47mm(L)
- Plunger length adjustable by top screw
- Stainless top screw and spring
- With plastic adaptor to fit the hole in the alarm cover
- No false alarm



WSF42 steel door 25mm

- Size: 25mm(Dia) x 30mm(L)
- Gap: 35mm
- Colour: white and brown



WSF52 tamper switch with plunger

- Size: 19mm(Dia) x 27mm(L)
- Quality reed tamper switch
- Comes with flange



WSF43 stubby press to fit

- Size: 9.5mm(Dia) x 19mm(L)
- Gap: 20mm
- Colour: white and brown

All Reed Switches come with standard wire 22 AWG 18" in length.