

# DH-IPC-HFW5442E-S

4MP WDR IR Bullet AI Network Camera



- 1/1.8" 4Megapixel progressive scan CMOS
- H.265&H.264 triple-stream encoding
- 25/30fps@2688×1520
- WDR(120dB), Day/Night(ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens (3.6mm/6mm optional)
- Max. IR LEDs Length 50m
- Micro SD memory, IP67

Dahua AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provides higher flexibility and accuracy for end-users. This enables the Dahua AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, traffic data statistics, etc. The complete lineup of Dahua AI includes network (PTZ) cameras, network video recorders, servers, and platform management products. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way.



## System Overview

Pro AI series contains Face Capture, Perimeter Protection and People Counting functions. Powered by deep-learning Artificial Intelligence algorithms, significantly improved accuracy. Meanwhile, the series features starlight and smart IR technology. This series fully protected from dust and water, certified to IP67 standard.

## Functions

### Perimeter Protection

Dahua's Perimeter Protection functions significantly improved accuracy. Perimeter Protection reduces false alarms and decreases pixel count requirements for object detection. Perimeter Protection features custom tripwires based on object type for automation in limited access areas such as pedestrian or vehicle-only zones. This combination of advanced AI analytics and real-time alerts to a desktop or to a mobile client reduces system requirements and resources resulting in greater surveillance system efficiency.

### People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

### Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Dahua face detection camera can extract six facial attributes and output the metadata for analysis.

### Protection(IP67, wide voltage)

The camera allows for  $\pm 30\%$  input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67), the camera is the choice for installation in even the most unforgiving environments.

Technical Specification						
Camera						
Image Sensor		1/1.8" 4Megapixel progressive scan CMOS				
Effective Pixels		2688(H) x 1520(V)				
RAM/ROM		512MB/128MB				
Scanning System		Progressive				
Electronic Shutter Speed		Auto/Manual, 1/3~1/100000s				
Minimum Illumination		0.0016Lux/F1.6 ( Color,1/3s,30IRE) 0.015Lux/F1.6 ( Color,1/30s,30IRE) 0Lux/F1.6(IR on)				
IR Distance		Distance up to 50m (164ft)				
IR On/Off Control		Auto/ Manual				
IR LEDs		2				
Lens						
Lens Type		Fixed				
Mount Type		Board-in				
Focal Length		2.8mm,3.6mm,6.0mm				
Max. Aperture		F1.6				
Angle of View		H: 113°, V:60°/H: 89°, V:48°/H: 56°, V:31°				
Optical Zoom		N/A				
Aperture Type		Fixed				
Close Focus Distance		1.3m(4.27ft)/1.9m(6.23t)/3.8m(12.47ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify	
	2.8mm	58m(190ft)	23m(75ft)	12m(39ft)	6m(20ft)	
	3.6mm	72m(236ft)	29m(95ft)	14m(46ft)	7m(23ft)	
	6.0mm	113m(371ft)	45m(148ft)	23m(75ft)	11m(36ft)	
Pan/Tilt/Rotation						
Pan/Tilt/Rotation Range		Pan:0°~360°; Tilt:0°~90°; Rotation:0°~360°				
Artificial Intelligence						
Perimeter Protection		Tripwire, Intrusion(Human & Vehicle classification)				
People Counting		Line crossing people counting, Region people counting				
General Intelligence						
Event Trigger		Motion detection, Video tampering , Scene changing, Network disconnection , IP address conflict, Illegal Access,Storage anomaly				
General Intelligence		Object Abandoned/Missing				
Video						
Compression		H.265+/H.265/H.264+/H.264/H.264B/H.264H/MJPEG(sub stream)				
Streaming Capability		3 Streams				
Resolution		2688×1520/2304×1296/1080P(1920×1080)/1.3M(1280×960)/720P(1280×720)/D1(704×576/704×480)/VGA(640×480)/CIF(352×288/352×240)				

Frame Rate	Main Stream: 2688×1520(1~25/30fps)
	Sub Stream: D1(1~25/30fps)
	Third Stream: 1080P(1~11fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 32~ 8192Kbps H.265: 19~ 8192Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detetion	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A
Smart IR	Support
Defog	Support
Digital Zoom	N/A
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio

Compression	N/A
-------------	-----

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP;SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; SNMP;QoS; UPnP;NTP
Interoperability	ONVIF(Profile S/Profile G), CGI,Milestone,Genetec,P2P
Streaming Method	Unicast / Multicast
Max. User Access	20 Users
Edge Storage	NAS FTP Mirco SD card 256GB
Web Viewer	IE(versions newer than IE8), Chrome, Firefox, Safari(versions newer than Safari 12)
Management Software	Smart PSS, DSS, P2P
Smart Phone	iOS, Android

Certifications

Certifications	CE-LVD:EN60950-1 CE-EMC:Electromagnetic Compatibility Directive 2014/30/EU FCC:47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
----------------	---

## Interface

Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A

## Electrical

Power Supply	DC12V(±30%), PoE(802.3af)(Class 0)
Power Consumption	DC12V:2.4W 5.7W(IR on) PoE:3W 6.8W(IR on)

## Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / 10%RH~95% RH
Storage Conditions	+5° C ~ +40° C (+41° F ~ +104° F) (daily temperature difference within 15° C/59° F) / 10%RH~95% RH
Ingress Protection	IP67
Vandal Resistance	N/A

## Construction


Casing	Metal,plastic
Dimensions	182.3mm×70.0mm×70.0mm (7.18"×2.76"×2.76")
Net Weight	0.47Kg (1.04lb)
Gross Weight	0.59Kg (1.30lb)

## Ordering Information

Type	Part Number	Description
4MP camera	DH-IPC-HFW5442EP-S	4MP WDR IR Bullet AI Network Camera, WDR,PAL
	DH-IPC-HFW5442EN-S	4MP WDR IR Bullet AI Network Camera, WDR,NTSC
	IPC-HFW5442EP-S	4MP WDR IR Bullet AI Network Camera, WDR,PAL
	IPC-HFW5442EN-S	4MP WDR IR Bullet AI Network Camera, WDR,NTSC
Accessories (optional)	PFA121	Junction box
	PFA152-E	Pole Mount
	PFA151	Corner Mount

## Accessories

## Optional:

PFA121  
Junction boxPFA152-E  
Pole MountPFA151  
Corner Mount

Junction Mount	Pole Mount	Corner Mount
PFA121	PFB121 + PFA152	PFB121 + PFA151

## Dimensions (mm/inch)

