

# DHI-NVR4432-I

## 32Channel 1.5U WizSense Network Video Recorder



WizSense

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

### System Overview

Dahua new NVR4000-I network video recorder delivers excellent performance and high recording quality that is ideally suitable for IP video surveillance applications. This NVR adopts powerful processor, providing the capability of 4K resolution processing for applications where image details are highly required. Besides, the NVR supports input, recording and transmission functions. Additionally, the NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

With build-in deep learning module, NVR4000-I series products adopt video image structuring technology based on deep learning algorithms, achieving high-precision human face recognition and perimeter protection. By applying deep learning artificial intelligence, NVR4000-I allows users to focus on what matters most, improves event response time and helps make video actionable.

The NVR is compatible with numerous third-party devices, which make it the perfect solution for surveillance systems that work independently of video management system (VMS).

### Functions

#### Perimeter Protection

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

#### Real Time Face Recognition

Video stream & picture stream real time face recognition. Facial attributes analysis features including gender, age, expression, glasses, moustache, mouth mask. Identify people and also capture, record faces with metadata. Facial feature filtering while real time display, only show faces with target features.

- 32 Channel IP video access
- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 4 Channel perimeter protection
- Up to 2 Channel video stream face recognition/8 channel picture stream face recognition ( with FD camera)
- Up to 12 face pictures /sec processing
- Up to 10 face databases with 20,000 face images in total



### Face Database Management

Configurable multiple face databases. Powerful face database management. Face database can be applied to video channels independently. Name, gender, birthday, address, certificate type, certificate No., countries&regions and state can be added to each face picture.

### Common/Stranger Mode

NVR4000-I supports common and stranger mode. In stranger mode, when NVR detects a strange face(not in device's face database), it can trigger alarm, buzzer, snapshot, record, etc. Similarity threshold can be set manually. This function is developed for important infrastructure sites for which access control is critical.

### AI Search

Support search by metadata of human and vehicles. Support uploading face pictures to NVR and compare them with recorded faces in NVR by similarity. Enable operators to quickly and easily search through multi channels and long duration, efficiently find out when and where a person of interest appear.

### ANPR

Automatic Number Plate Recognition available for convenient entrance/exit management. Support license plate recognition(working with Dahua ITC camera), black/white list import/export, add/delete B/W list number, search result from recorded video.

## Technical Specification

### System

|                  |                               |
|------------------|-------------------------------|
| Main Processor   | Multi-core embedded processor |
| Operating System | Embedded LINUX                |

### Perimeter Protection

|                       |  |
|-----------------------|--|
| Performance           | 4 channel, 10 IVS rules for each channel                       |
| Object classification | Human/Vehicle secondary recognition for tripwire and intrusion |
| AI Search             | Search by target classification (Human, Vehicle)               |

### Face Recognition

|                      |  |
|----------------------|--|
| Performance          | Max 12 face pictures /sec processing<br>2 channel video stream face recognition / 8 channel picture stream face recognition ( with FD camera)  |
| Stranger Mode        | Detect strangers' faces(not in device's face database). Similarity threshold can be set manually.  |
| AI Search            | Up to 8 target face images search at same time, similarity threshold can be set for each target face image.  |
| Database Management  | Up to 10 face databases with 20,000 face images in total. Name, gender, birthday, address, certificate type, certificate No., countries&regions and state can be added to each face picture. |
| Database Application | Each database can be applied to video channels independently.  |
| Trigger Events       | Buzzer, Voice Prompts, Email, Snapshot, Recording, Alarm Out, PTZ Activation, etc.   |

### Audio and Video

|                 |  |
|-----------------|--|
| IP Camera Input | 32 Channel                             |
| Two-way Talk    | 1 Channel Input, 1 Channel Output, RCA |

### Display

|                      |   |
|----------------------|---|
| Interface            | 1 HDMI, 1 VGA   |
| Resolution           | HDMI/VGA: 3840 x 2160, 1920 x 1080 , 1280 x 1024, 1280 x 720 , 1024 x 768 |
| Decoding Capability  | 2-ch@8MP(30fps), 8-ch@1080P(30fps)  |
| Multi-screen Display | 1/4/8/9/16  |

### Recording

|                 |  |
|-----------------|--|
| Bandwidth       | 200Mbps (80Mbps when AI function enabled, based on Dahua private protocol)       |
| Compression     | Smart H.265+/H.265/Smart H.264+/H.264/MJPEG                                      |
| Resolution      | 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.                       |
| Record Mode     | Manual, Schedule (Continuous, MD (Motion Detection) , Alarm, IVS)                |
| Record Interval | 1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec |

### Video Detection and Alarm

|                 |  |
|-----------------|--|
| Trigger Events  | Alarm Out, Video Push, Email, Recording, PTZ, Tour, Snapshot, Voice Prompt, Buzzer and Screen Tips |
| Video Detection | Motion Detection, MD Zones: 396 (22 x 18), Video Loss, Tampering and Scene Change                  |
| Alarm Input     | 16 Channel   |
| Alarm Output    | 4 Channel  |

## Playback and Backup

|               |   |
|---------------|---|
| Sync Playback | 1/4/9/16  |
| Search Mode   | Time /Date, Alarm, MD and Exact Search (accurate to second) |
| Backup Mode   | USB Device/Network  |

### Third-party Support

|                     |   |
|---------------------|---|
| Third-party Support | Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, Xunmei, Samsung, Sanyo, Sony, Watchnet and more |
|---------------------|---|

### Network

|                  |  |
|------------------|--|
| Interface        | 2 RJ-45 Port (10/100/1000Mbps)   |
| PoE              | N/A  |
| Network Function | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Center, IP Search (Support Dahua IP camera, DVR, NVS, etc.), P2P |
| Max. User Access | 128 users  |
| Mobile App       | iPhone, iPad, Android  |
| Interoperability | ONVIF (Profile S), SDK, CGI  |

### Storage

|              |  |
|--------------|--|
| Internal HDD | 4 SATA III Ports, Up to 8 TB capacity for each HDD |
| eSATA        | NA   |

### Auxiliary Interface

|       |   |
|-------|---|
| USB   | 2 USB Ports (1 Rear USB 3.0 , 1 Front USB 2.0 ) |
| RS232 | 1 Port, for PC Communication and Keyboard       |
| RS485 | 1 Port, for PTZ Control                         |

### Electrical

|                   |                          |
|-------------------|--------------------------|
| Power Supply      | Single, AC100-240V, 1.9A |
| Power Consumption | NVR: <7.0W (Without HDD) |

### Environmental

|                      |  |
|----------------------|--|
| Operating Conditions | -10°C to +55°C (+14°F to +131°F), 86 –106kpa |
| Storage Conditions   | 0°C to +40°C (+32°F to +104°F), 30–85% RH    |

### Construction

|              |  |
|--------------|--|
| Dimensions   | 1.5U, 440.0mm x 411.1mm x 76.0mm (17.32" x 16.19" x 2.99") |
| Net Weight   | 4.3kg (9.5 lb) (without HDD)                               |
| Gross Weight | 6.3kg (13.9 lb) (without HDD)                              |


### Certifications

|     |   |
|-----|---|
| CE  | EN55035, EN55032, EN55024, EN50130-4, EN60950-1 |
| FCC | Part 15 Subpart B, ANSI C63.4-2014              |

### Ordering Information

| Type                    | Model         | Description                                     |
|-------------------------|---------------|---|
| 32 Channel WizSense NVR | DHI-NVR4432-I | 32 Channel 1.5U WizSense Network Video Recorder |

### Dimensions (mm[inch])



### Panels

