

DHI-LM32-F210

32" FHD Monitor



Features:

- · Light and cost-effective plastic housing
- · suitable for continuous 24/7 operation
- \cdot 178°H/178°V extra-wide viewing angle for overall viewing performance
- · High fidelity digital processing for a brilliant and vivid video
- · 8ms fast response time with no image blurring or ghosting
- · Support multiple signal inputs such as HDMI, VGA and USB
- · Physical button and infrared remote dual control mode
- · Low energy consumption, long service life

| Technical Specification | | |
|-------------------------|-------------------------------|--|
| Model | | |
| Model | DHI-LM32-F210 | |
| Display | | |
| Screen Size | 31.5" | |
| Aspect Ratio | 16:9 | |
| Resolution | 1920×1080 (FHD) | |
| Backlight | LED | |
| Brightness/Luminance | 250 cd/ m² | |
| Contrast | 1400:1 | |
| Display Color | 16.7M(8bit) | |
| Viewing Angle(H/V) | 178°(H)/178°(V) | |
| Response time | 8ms | |
| Refresh Rate | 60Hz | |
| Signals | | |
| Input | VGA×1, HDMI×1 , | |
| General | | |
| Power Supply | AC100~240V (+/-10%), 50/60 Hz | |
| | | |

| Consumption (Standard) | 55W | | |
|------------------------------------|-----------------------------------|-----------------------|--|
| Consumption (Standby) | ≤0.5W | | |
| Туре | Internal | | |
| Net Weight | TBD | | |
| Gross Weight | TBD | | |
| Bezel Width | TBD | | |
| Wall Mount | 100×100mm | | |
| Dimension without standard (W×H×D) | TBD | | |
| Package(W×H×D) | TBD | | |
| Work Environment | Temperature | 0°C~40°C (32°F~104°F) | |
| work environment | Humidity | 20%~85% | |
| Accessory | | | |
| Standard | HDMI cable, power cable, pedestal | | |
| Optional | Hanging bracket | | |
| Certifications | | | |
| Certifications | CE/FCC | | |
| | | | |