

CAT6 UTP Slim Patch Cable

W26XX



FEATURES

- All Datamaster® network patch cables are Fluke® tested and exceed Australian standards.
- ISO/IEC 11801 Category 6 and TIA/EIA-568-C.2 Category 6 compliant.
- Supports performance up to 250MHz. Suitable for Fast Ethernet, Gigabit Ethernet and other network protocols.
- Backward compatible with Cat5e, Cat5 and Cat3 standards.
- Ultra-slim 3.6mm diameter, approximately 40% smaller than standard patch cables.
- Bend radius of 22 to 24mm for improved flexibility in tight spaces.
- Slim profile enhances airflow in crowded server racks and cabinets.
- Ideal for use where space is restricted.
- Made with 100% oxygen-free copper for high-quality performance.
- LSZH (Low Smoke Zero Halogen) jacket for safer installations.
- Unshielded Twisted Pair (UTP) construction with 4 twisted pairs and 8 multi-strand conductors.
- Wired to T568A colour code.
- RJ45 to RJ45 connectors with high-quality injection-moulded strain relief.
- 50µm gold-plated contacts with Category 6 compliant 2-row staggered pin plug.
- Snagless boots for easier cable handling and reduced snagging.
- Supplied in Datamaster® hang-cell packaging.
- POE++ compatible.
- Backed by our exclusive limited lifetime warranty.
- Custom-made cables available, including specific lengths, colours and customer-branded printing. Contact us to discuss your needs.

DESIGN & CONSTRUCTION



To view Access' extensive ranges go to: www.accesscomms.com.au

Sydney (Head Office)
Brisbane Sales
Melbourne Office
Adelaide Office

Unit 1, 29 Prince William Drive, Seven Hills NSW 2147
28 The Gateway, Broadmeadows VIC 3047
71 Anzac Highway, Ashford SA 5035

Phone: (02) 9414 8888
Phone: (07) 3308 5555
Phone: (03) 9330 8333
Phone: (08) 8338 5540

sales@accesscomms.com.au
brisbane@accesscomms.com.au
melbourne@accesscomms.com.au
adelaide@accesscomms.com.au

CAT6 UTP Slim Patch Cable

W26XX

1	Cable	UTP CAT6 CABLE 4P * 28AWG
2	Connection	P1 & P2 : 8P8C PLUG, LONG BODY, GOLD PLATED
3	Jacket material	LSZH, BLUE COLOUR
4	Packing	Flat patch cable packed in one polybag
5	Cable Printing	DATAMASTER  E4073 VERIFIED CAT6 PATCH CORD ANSI/TIA 568 A/B/568C.2 #28AWG 4PR

CHARACTERISTICS

COLOUR	LENGTHS	SKUS
BLUE	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m, 10.0m	W2640SLIBLU, W2650SLIBLU, W2648SLIBLU, W2651SLIBLU, W2652SLIBLU, W2653SLIBLU, W2655SLIBLU, W2660SLIBLU
YELLOW	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIYEL, W2650SLIYEL, W2648SLIYEL, W2651SLIYEL, W2652SLIYEL, W2653SLIYEL, W2655SLIYEL
GREEN	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIGRN, W2650SLIGRN, W2648SLIGRN, W2651SLIGRN, W2652SLIGRN, W2653SLIGRN, W2655SLIGRN
PINK	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIPNK, W2650SLIPNK, W2648SLIPNK, W2651SLIPNK, W2652SLIPNK, W2653SLIPNK, W2655SLIPNK
RED	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIRED, W2650SLIRED, W2648SLIRED, W2651SLIRED, W2652SLIRED, W2653SLIRED, W2655SLIRED
WHITE	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIWHI, W2650SLIWHI, W2648SLIWHI, W2651SLIWHI, W2652SLIWHI, W2653SLIWHI, W2655SLIWHI
BLACK	0.25m, 0.5m, 1.0m, 1.5m, 2.0m, 3.0, 5.0m	W2640SLIBLK, W2650SLIBLK, W2648SLIBLK, W2651SLIBLK, W2652SLIBLK, W2653SLIBLK, W2655SLIBLK

COMPLIANCE

- RoHS III EU/2015/863
- REACH SVHC x 219 (EC 1907/2006)
- ISO/IEC 11801 Category 6
- TIA/EIA-568-C.2
- AS/CA S008:2020



COLOURS

To view Access' extensive ranges go to: www.accesscomms.com.au

Sydney (Head Office)
Brisbane Sales
Melbourne Office
Adelaide Office

Unit 1, 29 Prince William Drive, Seven Hills NSW 2147
28 The Gateway, Broadmeadows VIC 3047
71 Anzac Highway, Ashford SA 5035

Phone: (02) 9414 8888
Phone: (07) 3308 5555
Phone: (03) 9330 8333
Phone: (08) 8338 5540

GREEN

sales@accesscomms.com.au
brisbane@accesscomms.com.au
melbourne@accesscomms.com.au
adelaide@accesscomms.com.au

RED