

PentaCODE® Series Remotes

The PentaCODE® Series remotes designed in Australia by Elsema incorporates advanced technology to deliver reliable performance with outstanding value. The innovative dual coding system lets you choose between the traditional 12-way dipswitch coding or advanced encrypted coding, making setup flexible and effortless. Available in 2 or 4 button models, these remotes provide versatile control over multiple devices while matching individual style preferences.

Designed for performance you can count on, the PentaCODE® series remote control goes beyond expectations. Trusted across Australia and around the world, each remote is built for exceptional reliability and durability. Its sleek, modern design effortlessly complements any application and advanced features ensure control you can rely on. Perfect for automatic gates and a wide range of other applications, the PentaCODE® Series delivers a premium, dependable solution every time.

FEATURES

- Transmission on 5 different frequencies
- Small size keyring remote with 2 or 4 buttons
- Uses Frequency Hopping Spread Spectrum (FHSS)
- Dual Coding System; dip switch and encrypted code
- Intuitive & versatile design for simplicity with high security



www.elsema.com

WHY CHOOSE PENTACODE®

Secure & Flexible

The unique dual coding system gives you the choice between encrypted coding for maximum security or dipswitch coding for quick setup and easy replacements.

Multi-Device Control

With 2 or 4 button models available, a single PentaCODE® remote can operate multiple devices, making life more convenient.

Durable Everyday Use

Designed with quality materials, these remotes are built to handle the demands of daily use while maintaining long lasting performance.

Stylish Choices

A variety of colour options allow you to select a remote that not only performs well but also matches your personal style.

Trusted Worldwide

Compliance with various international standards ensures PentaCODE® remotes deliver reliable performance, security and quality worldwide.



TECHNICAL SPECIFICATIONS

Frequency 433MHz License Free Band	**Coding** Encrypted Coding or 12-way Dipswitch	**Channel Options** 2 Button 4 Button
Supply A23 Battery	**Custom Label Design** Yes. MOQ 100 pcs	**Usable Receivers** PCR433 series
Operating Distance Up to 200 metres	**Compliance** AS/NZS 4268, **CE** and **FCC** certified	**Accessories** SV100 – Sun visor bracket WB100 – Wall mount

SCAN ME

www.elsema.com