

K42917 Datasheet

Elvox Master or Slave 7" Monitor for K429XX Kit



Technical Data

- DC input: 24V
- 7" LCD TFT screen
- LCD resolution 1024 x 600 (RGB)
- Micro SD card slot: SDHC format,
- Memory size 8–32 GB, Speed class: Class4 - Class10
- Memory capacity: 100 images (video entryphone internal memory). With micro SD card: 1000 images, 128 videos
- Dimensions (mm)
 - 188.8 (L) x 113.6 (H) x 14.9 (D) (without wall support)
 - 188.8 (L) x 113.6 (H) x 18.4 (D) (with wall support)

Functions

- 7" capacitive touch screen monitor
 - Internal flash memory and micro SD card support
 - Automatic and manual video/image recording
 - Intercom function between indoor units (of the same family)
 - Adjustable brightness, colour and contrast
 - Adjustable ringtone volume and conversation volume
 - 6 selectable melodies
 - "Do not disturb" function
 - Multiple languages (Italian, English, French, German, Spanish, Portuguese, Greek, Dutch)
-

42920-P Datasheet

Elvox RFID Door Station for K429XX 7" Kit



Technical Data

- Operating temperature: (-25 °C; +55 °C)
- Relative operating humidity: from 0% to 90%
- Frequency range: 13,553-13,567 MHz
- RF transmission power: < 60 dBμA/m
- Dimensions (mm)
 - 90.5 (L) x 190 (H) x 33 (D) (without-rainproof cover)
 - 101.3 (L) x 198.8 (H) x 43.8 (D) (withrainproof cover)

Functions

- Due Fili audio-video unit with wide-angle camera
 - 130° horizontal wide angle
 - White LEDs for night vision
 - Protection degree: IP54
 - Protection degree against impact: IK07
 - Aluminium housing, vandal-resistant
 - Speaker volume adjustment
 - Backlit name plate and call button
 - Can be installed with or without rain guard (rain guard included)
 - Electric door lock and/or automatic door control
 - Surface-wall mount installation
 - NFC card reader (cards supplied separately)
 - Lock actuation button mounting frame
 - Camera mounting frame (optional camera)
-