

Miniature BNC Male Patch Cable



**BNC Male Patch Lead
400mm RG179 Cable
P/N: E30130141/RG179**

**1000mm RG179 Cable
P/N E30130112/RG179**

**2000mm RG179 Cable
P/N E30130122/RG179**

Features:

- High quality BNC Male Connectors
- Standard Length = 400mm, 1000mm and 2000mm
- Custom lengths can be arranged if required


Application:

This miniature patch cable is easier to install, has a tighter bending radius and a Teflon dielectric for stable performance.

Due to its size, it takes up less room in ducts, cavities and in racks compared to the more commonly used RG59 cable.



RG179



RG59

Ideal for Connecting directly between Video Hubs and DVR's or via BNC Patch Panel



Specifications:

BNC Male Characteristics Electrical

- Impedance 75 nominal ohm
- Frequency Range: DC to 1.5 GHz Standard.
- Voltage Rating: Up to 500 Vrms
- Dielectric Rating: Up to 1500 Vrms for 1 minute
- VSWR: 1.25 max
- Insertion loss 0.25dB + 0.1db @ 1 GHz.

Mechanical

- 2 stud bayonet coupling to M39012
- Center conductor is solder type

Materials

- Connector Body: Brass
- Pin: Brass
- Crimp Ferrule: Brass
- Insulator: PTFE

Finish

- Nickel
- Gold
- Nickel

EQL Networks & Security

Unit 20, 13 Swaffham Road
Minto NSW 2566
Australia

Postal Address:
P.O. Box 351
Minto NSW 2566
Australia

Tel: +61 2 9824 5680
Fax: +61 2 9824 5685
Email: sales@eql.com.au
Web: www.eql.com.au

ABN: 93 098 402 218