

# PRODUCT INFORMATION

## SLIMLINE ELECTRIC DROP BOLT MORTISE MOUNT



DB1260PTO (power to release) DB1260PTL (power to lock)

### PRODUCT DESCRIPTION

DB1260 is designed for narrow frame swing doors, and/or glass door mounting. The drop bolt body depth of 35mm will fit into a 44mm depth door frame. The drop bolt is available in either “power to lock” or “power to release” format. The DB1260 can be wired into any fire/smoke alarm or security access control system.

In “power to release” mode the drop bolt is factory pre-set with a 3 seconds time delay and buzzer on "A" setting (refer to technical information supplied with drop bolt).

| PART No.        | DB1260PTO (power to release)                                     | DB1260PTL (power to lock) |
|-----------------|--|---------------------------|
| FUNCTION        | Slimline mortise mount drop bolt                                 |                           |
| HOLDING FORCE   | Up to 300kg  |                           |
| VOLTAGE/CURRENT | 12VDC 1.15A(in-rush) 250mA holding                               |                           |
| APPROVALS       | 4 hour fire rated to A.S. and B.S. standards                     |                           |
| MONITORING      | Door sensor<br>Remote release<br>Bi-coloured LED<br>Audible tone |                           |
| SIZE            | L= 210 x W= 25 x D= 35mm   |                           |
| WEIGHT          | 0.7g   |                           |
| UNITS PER BOX   | 10 per box (7.5kg)   |                           |

**Mounting installation:** Suitable for mounting on wooden, metal, glass, aluminum and PVC door frames.

### Common Features

- ◆ Internal control circuits protect drop bolt pin from damage
- ◆ Power to lock or power to release (has to be specified)
- ◆ Auto lock function
- ◆ Built-in varistor (MOV) for surge protection
- ◆ Time delay setting at 0/3/6/10 secs
- ◆ 1 year warranty