

# Composite cable for Access Control (RS485 and OSDP)



## PRODUCT DESCRIPTION

**GLOCOMP2PS6C4CF8-200GRY** is a composite cable designed for interconnecting doors to access control panels using RS485 and OSDP data communications protocols.

## FEATURES

- Fast installation – Just one cable for all door requirements: Credential reader, REX/ Call point, Tongue sense, Handle Position, Lock power
- Grey sheath ideal for Government projects & tenders.
- Stranded conductors and flexible V90 PVC for easy pulling.
- Clear ABCDE 0123456789 markings for error free connection identification.
- Metre marking for precise estimation of remaining cable – less waste.
- Meets all Australian compliance requirements.
- Long 3 year warranty.

## TECHNICAL DATA

### Cable 1

- **Conductor:** 2 Pair x 2C x 7/0.3mm  $\pm$  0.005mm TC – Tinned Copper
- **Insulation:** 1.20mm  $\pm$  0.1mm HDPE
- **Insulation Colour:** Red, Black, White, Green
- **1st Shield:** 2 x Aluminium Foil / 2C
- **Sheath:** 5.50mm  $\pm$  0.2mm PVC
- **Sheath Colour:** Grey

### Cable 2

- **Conductor:** 4C x 14/0.2mm  $\pm$  0.005mm Bare Copper
- **Insulation:** 1.50mm  $\pm$  0.1mm PVC
- **Insulation Colour:** Red, Black, White, Blue
- **Sheath:** 4.80mm  $\pm$  0.2mm PVC
- **Sheath Colour:** White

### Cable 3

- **Conductor:** 6C x 14/0.2mm  $\pm$  0.005mm Bare Copper
- **Insulation:** 1.50mm  $\pm$  0.1mm PVC
- **Insulation Colour:** Red, Black, White, Blue, Yellow, Green
- **Sheath:** 5.80mm  $\pm$  0.2mm PVC
- **Sheath Colour:** White

### Cable 4

- **Conductor:** 2C x 24/0.2mm  $\pm$  0.005mm Bare Copper
- **Sheath:** 2.8 x 5.5  $\pm$  0.1mm PVC
- **Sheath Colour:** White with Black Stripe

### Outer Sheath

- **Material:** PVC
- **Nominal O.D:** 15.0mm  $\pm$  2.0mm
- **Colour:** Grey
- **Tension before aging:**  $\geq$  10MPa
- **Breaking elongation before aging:**  $\geq$  125%
- **Breaking elongation after aging:**  $\geq$  100%

### Properties

- **Temperature:** -20°C up to +75°C
- **Lengths:** 200m Wooden Reel
- **Rip Cord:** Yes



**Drum Dimensions**  
440mm W x 440mm D  
x 160mm H

### Part Number

GLOCOMP2PS6C4CF8  
-200GRY

**Weight**  
42kg (200m) Pack

**Warranty**  
3 Year

**Compliance**  
AS/CA S008:2020  
AS/NZS 1660.5.6  
RoHS Compliant  
RCM



**Easy  
to strip  
jacket**



**Metre  
countdown  
marking**



**Ripcord  
beneath  
the sheath**



**Stranded  
conductors,  
flexible PVC**