



KINGDOM ELECTRONICS CC

Electronic Design and Manufacture
Security & Access Control Equipment

PO Box 1940 • HONEYDEW • 2040
Tel: (011) 791 1362/3749 • Fax: (011) 791 6610

CK 1991 /002586 / 23 VAT Reg No. 4130137047

E-mail: ke-sa@mweb.co.za Website: www.kesa.co.za

TECHNICAL PRODUCT BULLETIN

Code Hopping Receiver

Application


- ▶ Code Hopping secure receiver for new installations, gate/garage.

Specifications

- ▶ 12v-24v DC operation.
- ▶ Single channel receiver, range up to 100m.
- ▶ 433Mhz.
- ▶ Selectable relay times, pulse/latch.
- ▶ 1A relay contact rating.
- ▶ Easy to program transmitters, stores up to 80 transmitters.
- ▶ Physical size: 65mm x 45mm x 20mm.

Wiring Diagram

12-24v +
12-24v -
TRIGGER IN
Relay COM
Relay NC
Relay NO



Installation

- ▶ Connect DC voltage and relay trigger.
- ▶ Press and hold ADD button while transmitting from the remote.
- ▶ LED will flash to confirm learning of transmitter.
- ▶ Press the remote again to ensure the relay operates, repeat for additional transmitters.

QT06-002-A