

DHI-HY-MRF50-R9

Wireless Interconnected Module



- Compatible with Wisualarm mains powered alarms
- Wireless interconnected with maximum of 24 WisuLink RF devices
- RF mesh interconnected architecture
- Simply plug in module design
- Powered from Alarm head

System Overview

The product is an optional add-on wireless interconnected module for the Wisualarm mains-powered alarm units. It enables the Alarm to communicate wirelessly with other WisuLink devices. Up to 24 devices can be interconnected.


Technical Specification

Power Supply	Powered from Alarm
RF Range	A minimum of 100 metres in free space
RF Visual Indicator	Flashing Red: RF transmission Flashing Blue: Successfully interconnected
RF Frequency	925MHz
Interconnect	Up to 24 WisuLink RF devices
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	≤95% RH (non condensing)
Color	White
Casing	PC+ABS
Dimensions	53.5 mm × 38.2 mm × 11.7 mm (2.11" × 1.50" × 0.46")
Weight	11.9 g (0.03 lb)
Compliance Standard	AS/NZS 4268:2017

Ordering Information

Type	Part Number	Description
Wireless Module	DHI-HY-MRF50-R9	Wireless Module

Installation



Dimensions (mm/inch)

