

CORRUGATED CONDUIT



SOLAR HD

FEATURES & BENEFITS

- Highly flexible | Heavy duty PVC
- Metre marked – easy measure
- High impact strength | Crush resistant
- Flame retardant | Self-extinguishing
- Extreme UV Resistant.
- BEP Certified

PACKED DETAILS

Size:	47 x 47 x 24cm (M25) 42 x 42 x 20cm (M32)
Weight:	8kg
QTY/pallet	25

SPECIFICATIONS

Size / length:	25mm x 50m (M25) 32mm x 25m (M32)
Material:	U-PVC Self-extinguishing Flame retardant
Ingress protection (IP):	IP66
Resistance to compression:	Min 1250Nt / 5cm
Complies to:	AS/NZS 2053.5:2001 AS/NZS 5033:2012
Colour:	Grey and black
Minimum inside diameter:	18mm/25mm
Outside diameter:	24.8 - 25mm/31.7-32mm
Temp. range:	-5°C to +60°C



CORRUGATED CONDUIT

Code	Description	Packing	MOQ	Ctn
CC-M25/50M-PV	Corrugated Conduit Solar HD - Grey 25mm x 50m	1	1	35/pallet
CC-M25/50M-PV-B	Corrugated Conduit Solar HD - Black 25mm x 50m	1	1	35/pallet
CC-M32/25M-PV	Corrugated Conduit Solar HD - Grey 32mm x 25m	1	1	35/pallet