



## remote access transmitters - Series 4 AK4 models

The Airkey has been updated but, as always, maintained backward compatibility with previous generations of Airkeys.

Now with just three models, the AK2, AK4 and AK6, the case has been re-designed to be stronger, with improved sealing and with a screw for easier opening, and all share the same diecast surround.

The internal electronics is carried over from the Series 3 Airkey, designed with a custom programmed RF transmitter/microcontroller providing the same high security rolling code encryption that ensures codes cannot be recorded and duplicated.

- 4 button remote control transmitter
- IP65 environmental resistance
- Dimensions: 63 x 35.5 x 12 mm, 26g
- ASK (OOK) transmission at 433.92MHz, ~40uW EIRP
- 69 bit encrypted packets with 32 bit serial number
- Powered by long life CR2032 lithium/manganese button cell
- Available programmed for standalone use or for access control
- 26(STD), 27, 30, 32, 34, 35, 37 & 38-bit Wiegand formats available
- Available fitted with 26-bit HID eprox disc
- Other types/formats of eprox discs may be installed on request
- Compatible with AKRX62-P, AKRX62-S, AKRX64-S, AKRX61-Wnn and AKRX64-Wnn receivers  
( Depending on type/format of Airkey )

### Types available:

AK4	4-button standalone transmitter
AK4-W26	4-button 26-bit Wiegand transmitter
AK4-W26H	4-button 26-bit Wiegand transmitter with HID eprox disc
AK4-Wnn	4-button nn-bit Wiegand transmitter on request

Designed and manufactured by Neatrol Systems

AIRKEY® is a registered trademark of Neatrol Holdings Pty Ltd