

Specifications - WS-8-150-DC

Manufactured / Assembled	North America
Standard 19" rack mount / Desktop / Wall mount	YES
Dimensions	191mm x 178mm x 44mm
Weight	2 kg
Power Input (Positive DC only)	9-72 VDC
Chassis Earth Ground Lug	YES
Power Consumption	6-10 watts without POE budget
Intelligent Forced Air Cooling With Fan RPM Monitoring	YES
Switch Core and PHYs	Vitesse
Processor	MIPS 24K 416 MHz
System Memory	128 MB
Flash Storage	16 MB
Total Non-Blocking Line Rate	14 Gbps
Certifications	CE, FCC, IC
Operating Temperature	-25 to 55°C (-13 to 131° F)
Operating Humidity	5 to 95% Non-Condensing
Console Port	RS-232
Ethernet Ports	(3) 10/100/1000 Ethernet Ports (2) SFP Ports
Passive POE Configured Per Port via UI / CLI	24V 1A pins 4,5(+) 7,8(-) 48V 1A pins 4,5(+) 7,8(-) 48VH 2A pins 1,2,4,5(+) 3,6,7,8(-)
POE Out Voltage Range	50 VDC / 24 VDC
Passive POE Current Sensors Per Port	YES
ESD Rating	24 kV Air / 24 kV Contact

24V POE Ports Pins 4,5 (+) Pins 7,8 (-) .75A	48V POE Ports Pins 4,5 (+) Pins 7,8 (-) .75A	48VH POE Ports Pins 1,2,4,5 (+) Pins 3,6,7,8 (-) 1.5A
Ports 01-08	Ports 01-08	Port 01

