

FEATURES

- Ergonomic design
- Australian output plugs
- Wide input voltage range
- Boost and buck AVR
- Compatible with generators
- Audible alarms function
- Full-time surge protection
- Automatic diagnostic on startup
- Cold start function
- Intelligent battery management
- Automatic restart when mains returns
- **USB** communication
- Supplied with intelligent monitoring and control software
- Protection against short circuit and low battery voltage





















Surveillance

Systems












SPECIFICATIONS

FRONT PANELS




1 - Power switch 2 - LED indicators -

AC mode: green LED on Battery mode: yellow LED flashing

Fault mode: red LED on

2)		
	\(\frac{1}{2}\)	

BACK PANELS



- 1 USB communication port
- 2 RJ45 surge protection
- 3 IEC input
- 4 User replaceable fuse
- 5 Output sockets

Model	ECO-ALTO1400					
Capacity	1400VA/840W					
Input	1400 VA 040 VV					
Voltage	230/240V					
AVR voltage range	230/240V 162V-290V					
Frequency range	40Hz-70Hz					
Output	40112-70112					
Voltage regulation	Batt. mode: 230V ± 10%					
Frequency	50 Hz ± 1Hz AC mode: sine wave; Battery mode: simulated sinewave					
Waveform						
Transfer time	Typical 2-6ms					
Battery						
Турв	Sealed lead acid, maintenance free					
Configuration	2 x 12V/7.5AH					
Charge current(Max)	2A					
Backup time	> 6 minutes load dependent					
Recharge	6-8 hours to 90% capacity after complete discharge					
Function						
Communication	USB					
Surge protection	RJ45					
DC start	Yes					
Auto restart	Yes					
AVR	Yes					
Surge protection	720 Joules / 30000A					
Input protection	EN50091-2 (C-Tick)					
Short circuit	User replaceble fuse					
LED indication &audible alarms	AC mode, battery charging, battery mode, battery low, over temperature, overload, short circuit					
Environment						
Audible noise	< 40dB					
Temperature	0 - 40 Degrees C(non-condensing)					
Humidity	0 - 90%					
Physical						
Australian outlets	3					
Dimensions (WxDxH)	125x380x225mm					
Net weight	8Kg					

RUNTIME IN MINUTES

Load VA/W	100VA	200VA	400VA	500VA	600VA	800VA	1000VA	1200VA
	60W	120W	240W	300W	360W	480W	600W	720W
ECO-ALTO1400	91	60	32	28	23	15	10	7