

Compact Enclosure - MSB

Manufactured in Europe

Features

- IP66, IK10 rating
- Powder coated mild steel 1.5mm
- Galvanised mounting plate installed
- Discreet with no external branding or markings
- Reversible door
- Colour - RAL7035

Accessories

- Keyed Lock
- Adjustable pole clamps
- Vented front door, IP54



Specifications

Model	Sizing(HxWxD)	Description
MSB.202015	200x200x150mm	IP66, 1.5mm Mild steel enclosure
MSB.303020	300x300x200mm	IP66, 1.5mm Mild steel enclosure
MSB.403020	400x300x200mm	IP66, 1.5mm Mild steel enclosure
MSB.403025	400x300x250mm	IP66, 1.5mm Mild steel enclosure
MSB.604020	600x400x200mm	IP66, 1.5mm Mild steel enclosure
MSB.806020	800x600x200mm	IP66, 1.5mm Mild steel enclosure

Model	Description
Vented door for mild steel enclosure	
MSVD.2020	IP54, vented door for MSB.202015 (1x Vent)
MSVD.3030	IP54, vented door for MSB.303020 (1x Vent)
MSVD.4030	IP54, vented door for MSB.403020/25 (2x Vent)
MSVD.6040	IP54, vented door for MSB.604020 (2x Vent)
MSVD.8060	IP54, vented door for MSB.806020 (4x Vent)
Pole Clamps	
BT2-MSG200	Galvanized/Zinc pole clamp for MSB.202015, 100mm to 300mm pole diameter (200 wide cabinet) (150Kgs)
BT2-MSG300	Galvanized/Zinc pole clamp for MSB.303020, 100mm to 300mm pole diameter (300 wide cabinet) (150Kgs)
BT2-MSG400	Galvanized/Zinc pole clamp for MSB.402020/25, 100mm to 300mm pole diameter (400 wide cabinet) (150Kgs)
BT2-MSG600	Galvanized/Zinc pole clamp for MSB.806020, 100mm to 300mm pole diameter (600 wide cabinet) (150Kgs)
Keyed lock	
STP.K2	Chromed keyed lock for MSB and SSB cabinets, (1x for 200-400 high, 2x for 600-800 high)

Specifications are subject to change without prior notice.