

# RollUPS

## UPS for 0.5-1Hp motors

**Retain battery power for weeks  
after a mains fail**

The Roll UPS systems was developed in consultation with industry specialists to meet specific needs of evacuation systems and automated door controls in Australian buildings.



Pro 1000M / Pro 1400M



XL+2000



### Features

- Sleep mode (Pro model only)
- Australian output plugs
- Compatible with generators
- LED indication and audible alarms function
- Full-time surge protection
- Intelligent battery management
- Automatic battery charging in UPS off mode
- Cold start function
- Retains battery power
- Protection against short circuit and low battery voltage
- Suits existing 240V single phase motor loads up to 484W
- Provide power for a minimum of 20 door or gate operation cycles

## Specifications

Model	Pro 1000M	Pro 1400M	XL+2000		
Capacity	Motors to 0.5Hp	Motors to 0.5Hp	Motors to 1Hp		
<b>Input</b>					
Voltage	230V ± 25%				
AVR Voltage Range	165V-275V				
Frequency Range	40Hz-70Hz				
<b>Output</b>					
Voltage Regulation (Batt.Mode)	230V ± 10%				
Frequency	AC mode: tracks utility; Battery Mode: 50 Hz ± 0.5Hz				
Waveform	AC mode: sine wave; Battery mode: simulated sinewave	Pure sine wave			
Transfer Time	Typical 6ms	0ms			
<b>Battery</b>					
Type	Sealed lead acid, maintenance free				
Configuration	2 x 12V/7AH		4 x 12V/9AH		
Charge Current(Max)	2A		3A		
Recharge	8 hours to 90% capacity after complete discharge	90% within 4 hours			
<b>Function</b>					
Communication	Power Manager via USB				
Surge Protection	RJ11		RJ45		
DC start	Yes				
Auto Restart	Yes				
AVR	Yes				
Surge protection	720 Joules / 30000A		1600 Joules / 40000A		
Input protection	EN50091-2				
Short Circuit	Electronic and fuse				
LCD (for XL+2000)	UPS status, I/P & O/P voltage frequency, load %, battery voltage & %, temperature, model				
LED indication & audible Alarms	AC Mode, Battery Charging, Battery mode, Battery Low, Over Temperature, Overload, Short Circuit	Normal (Green), back up (Yellow), fault (Red)			
<b>Environment</b>					
Audible Nnoise	< 40dB				
Temperature	0 - 40 Degrees C( non-condensing)				
Humidity	0 - 95%				
<b>Physical</b>					
Outlets	3 Australian outlets				
Dimension(W*D*H)	143x408x197mm		440x410x132(3RU)		
Net weight	10.9Kg	11.1Kg	26.7Kg		

Specifications are subject to change without prior notice



N12754