

Compact Enclosure - SSB

Manufactured in Europe

Features

- IP66, IK10 rating
- Polished Stainless Steel 316 1.5mm
- Mounting plate pre-installed
- Discreet with no external branding or markings
- Stainless steel hinges
- Reversible door - rotate unit 180 degrees
- Clinch nuts
- Earth studs
- Cable management/ runner on the door



Accessories

- Keyed Lock-STP-K2
- Adjustable pole clamps - BT2-SSXX

Specifications

Model	Sizing(HxWxD)	Description
SSB.202015	200x200x150mm	IP66, 1.5mm Stainless Steel 316 enclosure
SSB.303020	300x300x200mm	IP66, 1.5mm Stainless Steel 316 enclosure
SSB.403020	400x300x200mm	IP66, 1.5mm Stainless Steel 316 enclosure
SSB.403025	400x300x250mm	IP66, 1.5mm Stainless Steel 316 enclosure
SSB.604020	600x400x200mm	IP66, 1.5mm Stainless Steel 316 enclosure
SSB.806020	800x600x200mm	IP66, 1.5mm Stainless Steel 316 enclosure

Model	Description
Pole Clamps	
BT2-SS200	Stainless steel 316 pole clamp for SSB.202015, 100mm to 300mm pole diameter (200 wide cabinet) (150Kgs)
BT2-SS300	Stainless steel 316 pole clamp for SSB.303020, 100mm to 300mm pole diameter (300 wide cabinet) (150Kgs)
BT2-SS400	Stainless steel 316 pole clamp for SSB.403020/25, 100mm to 300mm pole diameter (400 wide cabinet) (150Kgs)
BT2-SS600	Stainless steel 316 pole clamp for SSB.806020, 100mm to 300mm pole diameter (600 wide cabinet) (150Kgs)
Keyed lock	
STP.K2	Chromed keyed lock for MSB and SSB cabinets, (1x for 200-400 high, 2x for 600-800 high)

Specifications are subject to change without prior notice.