

2T8000 ASSET TAG

Product Information Sheet

The Protrac iD series of Active Tags are powered by an internal lithium battery. The tag will for the duration of its life transmit a Radio Frequency (RF) signal at a pre-set time interval. The tag life is estimated up to 5 years at a transmission time interval of approximately 1.5 seconds.

The transmitted tag data includes Customer Site Code (CSC), Tag ID, Tag Age Counter Value with the options of Movement Alarm and Tamper Alarm Status. Protrac iD Asset Tags are encapsulated in a moulded plastic case, which is ultrasonically sealed during the manufacturing process for adverse environmental conditions.

The 2T8000 is suited for operating on metallic surfaces (or plastics containing a high metal content) and is generally used for asset tagging applications. The affixing of a tag depends on the type of application the standard method is by VHB double-sided adhesive tape.



Features

- Active 24 x 7
- High Impact resistant UV stabilized PVC constructions
- Transmission largely unaffected by materials in the surrounding environment
- Easily fixed to all surfaces including metal
- Convenient size (60mm x 29mm x 13mm) for application to large and small assets
- Tags attached to road transport, rolling stock and cargo are monitored at up to 220 kph
- Tags are read by fixed, mobile or hand held receivers

Designed and Manufactured in Australia

All rights reserved. Specifications subject to change without notice.

