

Quick Overview

Cat6 UTP Patch Lead - 250MHz



Features

Cat6 Network Patch Leads

The Cat6 UTP patch leads conform to the TIA/EIA-568-B specification. Patch leads are wired to the T568A pinout specification. They are individually channel tested and are made with tangle free slimline injection moulded boots in various colours and lengths.

Cat6 UTP Patch Leads - 250MHz

- Produced by an ISO9001 and ISO14001 certified manufacturer
- 100% Tested & channel certified by 3P, UL & ETL
- Colour: Orange
- Length: 1.5m

Details

Part No.	DYNPLO-C6A-1H
Brand	DYNAMIX
Unit Of Measure	Each
Compendium Page #	467
Colour	Orange
Length	1.5m

Proudly Distributed By



☎ 1300 555 586

🌐 www.repelec.com.au

✍ Sign up or log in to repelec.com.au

📘 📷 ✕ 📺 @RepelecAU

Page 1

T568A Cabling Pinout Specifications

- 8 - Brown (R4)
- 7 - Brown/White (T4)
- 6 - Orange (R2)
- 5 - Blue/White (T1)
- 4 - Blue (R1)
- 3 - Orange/White (T2)
- 2 - Green (R3)
- 1 - Green/White (T3)

