

## Quick Overview

---

Cat6 UTP Patch Lead - 250MHz



## Features

---

### Cat6 Network Patch Leads

The Cat6 UTP patch leads conform to the TIA/EIA-568-B specification. Patch leads are wired to the T568A pinout specification. They are individually channel tested and are made with tangle free slimline injection moulded boots in various colours and lengths.

### Cat6 UTP Patch Leads - 250MHz

- Produced by an ISO9001 and ISO14001 certified manufacturer
- 100% Tested & channel certified by 3P, UL & ETL
- Colour: Orange
- Length: 2m

## Details

---

<b>Part No.</b>	DYNPLO-C6A-2
<b>Brand</b>	DYNAMIX
<b>Unit Of Measure</b>	Each
<b>Compendium Page #</b>	467
<b>Colour</b>	Orange
<b>Length</b>	2m

Proudly Distributed By



☎ 1300 555 586

🌐 [www.repelec.com.au](http://www.repelec.com.au)

✍ Sign up or log in to [repelec.com.au](http://repelec.com.au)

📱 [f](#) [@](#) [X](#) [v](#) @RepelecAU

Page 1

T568A Cabling Pinout Specifications

- 8 - Brown R4
- 7 - Brown/White T4
- 6 - Orange R2
- 5 - Blue/White T1
- 4 - Blue R1
- 3 - Orange/White T2
- 2 - Green R3
- 1 - Green/White T3

