

Quick Overview

Cat6 UTP Slimline Patch Lead - 250MHz



Features

Cat6 Network Patch Leads - Slimline

The New Slimline Cat6 UTP patch leads conform to the TIA/EIA-568-B specification. Patch leads are wired to the T568A pin out specification. They are component level tested and are made with tangle free slimline injection moulded boots and latch down plugs in various colours and lengths.

Cat6 UTP Slimline Patch Leads - 250MHz

- Produced by an ISO9001 and ISO14001 certified manufacturer
- 100% Tested & component level certified by 3P, UL & ETL
- High flexible bend radius
- Colour: Blue
- Length: 2m

Details

Part No.	DYNPLSE-C6-2
Brand	DYNAMIX
Unit Of Measure	Each
Compendium Page #	465
Colour	Blue
Length	2m

Proudly Distributed By



☎ 1300 555 586

🌐 www.repelec.com.au

✍ Sign up or log in to repelec.com.au

📱 [f](#) [@](#) [X](#) [v](#) @RepelecAU

Page 1

Additional Information

T568A Cabling Pinout Specifications

- ⑧ - Brown R4
- ⑦ - Brown/White T4
- ⑥ - Orange R2
- ⑤ - Blue/White T1
- ④ - Blue R1
- ③ - Orange/White T2
- ② - Green R3
- ① - Green/White T3

