

## Quick Overview

---

Cat6 UTP Slimline Patch Lead - 250MHz



## Features

---

### Cat6 Network Patch Leads - Slimline

The New Slimline Cat6 UTP patch leads conform to the TIA/EIA-568-B specification. Patch leads are wired to the T568A pin out specification. They are component level tested and are made with tangle free slimline injection moulded boots and latch down plugs in various colours and lengths.

### Cat6 UTP Slimline Patch Leads - 250MHz

- Produced by an ISO9001 and ISO14001 certified manufacturer
- 100% Tested & component level certified by 3P, UL & ETL
- High flexible bend radius
- Colour: Blue
- Length: 3m

## Details

---

<b>Part No.</b>	DYNPLSE-C6-3
<b>Brand</b>	DYNAMIX
<b>Unit Of Measure</b>	Each
<b>Compendium Page #</b>	465
<b>Colour</b>	Blue
<b>Length</b>	3m

Proudly Distributed By



☎ 1300 555 586

🌐 [www.repelec.com.au](http://www.repelec.com.au)

✍ Sign up or log in to [repelec.com.au](http://repelec.com.au)

📱 [f](#) [@](#) [X](#) [v](#) @RepelecAU

Page 1

# Additional Information

## T568A Cabling Pinout Specifications

- 8 - Brown
- 7 - Brown/White
- 6 - Orange
- 5 - Blue/White
- 4 - Blue
- 3 - Orange/White
- 2 - Green
- 1 - Green/White

